

Package ‘RcppSimdJson’

October 9, 2026

Type Package

Title 'Rcpp' Bindings for the 'simdjson' Header-Only Library for
'JSON' Parsing

Version 0.1.16

Date 2026-10-09

Description The 'JSON' format is ubiquitous for data interchange, and the 'simdjson' library written by Daniel Lemire (and many contributors) provides a high-performance parser for these files which by relying on parallel 'SIMD' instruction manages to parse these files as faster than disk speed. See the [doi:10.48550/arXiv.1902.08318](https://doi.org/10.48550/arXiv.1902.08318) paper for more details about 'simdjson'. This package parses 'JSON' from string, file, or remote URLs under a variety of settings.

License GPL (>= 2)

Imports Rcpp, utils

LinkingTo Rcpp

Suggests bit64, tinytest

URL <https://github.com/eddelbuettel/rcppsimdjson/>

BugReports <https://github.com/eddelbuettel/rcppsimdjson/issues>

Encoding UTF-8

Config/roxygen2/version 8.1.0

NeedsCompilation yes

Author Dirk Eddelbuettel [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-6419-907X>>),
Brendan Knapp [aut] (ORCID: <<https://orcid.org/0000-0003-3284-4972>>),
Daniel Lemire [aut] (ORCID: <<https://orcid.org/0000-0003-3306-6922>>)

Maintainer Dirk Eddelbuettel <edd@debian.org>

Repository CRAN

Date/Publication 2026-10-09 14:00:02 UTC

Contents

RcppSimdJson-package	2
fparse	3
is_valid_json	8
parseExample	11
release_json_memory	12
validateJSON	12
Index	14

RcppSimdJson-package	<i>'Rcpp' Bindings for the 'simdjson' Header-Only Library for 'JSON' Parsing</i>
----------------------	--

Description

The 'JSON' format is ubiquitous for data interchange, and the 'simdjson' library written by Daniel Lemire (and many contributors) provides a high-performance parser for these files which by relying on parallel 'SIMD' instruction manages to parse these files as faster than disk speed. See the <doi:10.48550/arXiv.1902.08318> paper for more details about 'simdjson'. This package parses 'JSON' from string, file, or remote URLs under a variety of settings.

Package Content

Index of help topics:

RcppSimdJson-package	'Rcpp' Bindings for the 'simdjson' Header-Only Library
fparse	Fast, Friendly, and Flexible JSON Parsing
is_valid_json	simdjson Utilities
parseExample	Simple JSON Parsing Example
release_json_memory	Release Memory Kept Between Calls
validateJSON	Validate a JSON file, fast

Maintainer

Dirk Eddelbuettel <edd@debian.org>

Author(s)

Dirk Eddelbuettel [aut, cre] (ORCID: <<https://orcid.org/0000-0001-6419-907X>>), Brendan Knapp [aut] (ORCID: <<https://orcid.org/0000-0003-3284-4972>>), Daniel Lemire [aut] (ORCID: <<https://orcid.org/0000-0003-3306-6922>>)

Description

Parse JSON strings and files to R objects.

Usage

```
fparse(  
  json,  
  query = NULL,  
  empty_array = NULL,  
  empty_object = NULL,  
  single_null = NULL,  
  parse_error_ok = FALSE,  
  on_parse_error = NULL,  
  query_error_ok = FALSE,  
  on_query_error = NULL,  
  max_simplify_lvl = c("data_frame", "matrix", "vector", "list"),  
  type_policy = c("anything_goes", "numbers", "strict"),  
  int64_policy = c("double", "string", "integer64", "always"),  
  always_list = FALSE  
)  
  
fload(  
  json,  
  query = NULL,  
  empty_array = NULL,  
  empty_object = NULL,  
  single_null = NULL,  
  parse_error_ok = FALSE,  
  on_parse_error = NULL,  
  query_error_ok = FALSE,  
  on_query_error = NULL,  
  max_simplify_lvl = c("data_frame", "matrix", "vector", "list"),  
  type_policy = c("anything_goes", "numbers", "strict"),  
  int64_policy = c("double", "string", "integer64", "always"),  
  always_list = FALSE,  
  verbose = FALSE,  
  temp_dir = tempdir(),  
  keep_temp_files = FALSE,  
  compressed_download = FALSE,  
  ...  
)
```

Arguments

json	JSON strings, file paths, or raw vectors. • fparse() – character: One or more JSON strings. – raw: json is interpreted as the bytes of a single JSON string. – list Every element must be of type "raw" and each is individually interpreted as the bytes of a single JSON string. • fload() – character: One or more paths to files (local or remote) containing JSON.
query	If not NULL, JSON Pointer(s) used to identify and extract specific elements within json. See Details and Examples. NULL, character(), or list() of character(). default: NULL
empty_array	Any R object to return for empty JSON arrays. default: NULL
empty_object	Any R object to return for empty JSON objects. default: NULL.
single_null	Any R object to return for single JSON nulls. default: NULL.
parse_error_ok	Whether to allow parsing errors. default: FALSE.
on_parse_error	If parse_error_ok is TRUE, on_parse_error is any R object to return when query errors occur. default: NULL.
query_error_ok	Whether to allow parsing errors. default: FALSE.
on_query_error	If query_error_ok is TRUE, on_query_error is any R object to return when query errors occur. default: NULL.
max_simplify_lvl	Maximum simplification level. character(1L) or integer(1L), default: "data_frame" • "data_frame" or 0L • "matrix" or 1L • "vector" or 2L • "list" or 3L (no simplification)
type_policy	Level of type strictness. character(1L) or integer(1L), default: "anything_goes". • "anything_goes" or 0L: non-recursive arrays always become atomic vectors • "numbers" or 1L: non-recursive arrays containing only numbers always become atomic vectors • "strict" or 2L: non-recursive arrays containing mixed types never become atomic vectors
int64_policy	How to return big integers to R. character(1L) or integer(1L), default: "double". • "double" or 0L: big integers become doubles • "string" or 1L: big integers become characters • "integer64" or 2L: big integers become bit64::integer64s • "always" or 3L: all integers become bit64::integer64s
always_list	Whether a list should always be returned, even when length(json) == 1L. default: FALSE.

verbose	Whether to display status messages. TRUE or FALSE, default: FALSE
temp_dir	Directory path to use for any temporary files. character(1L), default: tempdir()
keep_temp_files	Whether to remove any temporary files created by fload() from temp_dir. TRUE or FALSE, default: TRUE
compressed_download	Whether to request server-side compression on the downloaded document, default: FALSE
...	Optional arguments which can be use <i>e.g.</i> to pass additional header settings

Details

- Instead of using lapply() to parse multiple values, just use fparse() and fload() directly.
 - They are vectorized in order to leverage the underlying simdjson::dom::parser's ability to reuse its internal buffers between parses.
 - Since the overwhelming majority of JSON parsed will not result in scalars, a list() is always returned if json contains more than one value.
 - If json contains multiple values and has names(), the returned object will have the same names.
 - If json contains multiple values and is unnamed, fload() names each returned element using the file's basename().
- query's goal is to minimize the amount of data that must be materialized as R objects (the main performance bottleneck) as well as facilitate any post-parse processing.
 - To maximize flexibility, there are two approaches to consider when designing query arguments.
 - * character vectors are interpreted as containing queries that meant to be applied to all elements of json=.
 - If json= contains 3 strings and query= contains 3 strings, the returned object will be a list of 3 elements (1 for each element of json=), which themselves each contain 3 lists (1 for each element of query=).
 - * lists of character vectors are interpreted as containing queries meant to be applied to json in a zip-like fashion.

Value

A string with the parsed result.

Author(s)

Brendan Knapp

Examples

```
# simple parsing =====
json_string <- '{"a":[[1,null,3.0],["a","b",true],[1000000000,2,3]]}'
fparse(json_string)
```

```

raw_json <- as.raw(
  c(0x22, 0x72, 0x61, 0x77, 0x20, 0x62, 0x79, 0x74, 0x65, 0x73, 0x20, 0x63,
    0x61, 0x6e, 0x20, 0x62, 0x65, 0x63, 0x6f, 0x6d, 0x65, 0x20, 0x4a, 0x53,
    0x4f, 0x4e, 0x20, 0x74, 0x6f, 0x6f, 0x21, 0x22)
)
fparse(raw_json)

# ensuring a list is always returned =====
fparse(json_string, always_list = TRUE)
fparse(c(named_single_element_character = json_string), always_list = TRUE)

# controlling type-strictness =====
fparse(json_string, type_policy = "numbers")
fparse(json_string, type_policy = "strict")
fparse(json_string, type_policy = "numbers", int64_policy = "string")

if (requireNamespace("bit64", quietly = TRUE)) {
  fparse(json_string, type_policy = "numbers", int64_policy = "integer64")
}

# vectorized parsing =====
json_strings <- c(
  json1 = '["b":true,
    "c":null],
    {"b":[[1,2,3],
      [4,5,6]],
    "c":"Q"}]',
  json2 = '["b":[[7, 8, 9],
    [10,11,12]],
    "c":"Q",
    {"b":[[13,14,15],
      [16,17,18]],
    "c":null}]'
)
fparse(json_strings)

fparse(
  list(
    raw_json1 = as.raw(c(0x74, 0x72, 0x75, 0x65)),
    raw_json2 = as.raw(c(0x66, 0x61, 0x6c, 0x73, 0x65))
  )
)

# controlling simplification =====
fparse(json_strings, max_simplify_lvl = "matrix")
fparse(json_strings, max_simplify_lvl = "vector")
fparse(json_strings, max_simplify_lvl = "list")

# customizing what `[]`, `{}`, and single `null`s return =====
empties <- "[[],{},null]"
fparse(empties)
fparse(empties,
  empty_array = logical(),

```



```
# multiple queries applied to EACH element =====
fparse(json_to_query,
       query = list(queries_for_json1 = c(c1 = "/1/b/c/1/0",
                                           c2 = "/1/b/c/1/1"),
                    queries_for_json2 = c(d1 = "/1/b/d/1",
                                           d2 = "/1/b/d/2")))

# load JSON files =====
single_file <- system.file("jsonexamples/small/demo.json", package = "RcppSimdJson")
fload(single_file)

multiple_files <- c(
  single_file,
  system.file("jsonexamples/small/smalldemo.json", package = "RcppSimdJson")
)
fload(multiple_files)

## Not run:

# load remote JSON =====
a_url <- "https://api.github.com/users/lemire"
fload(a_url)

multiple_urls <- c(
  a_url,
  "https://api.github.com/users/eddelbuettel",
  "https://api.github.com/users/knapplly",
  "https://api.github.com/users/dcooley"
)
fload(multiple_urls, query = "name", verbose = TRUE)

# download compressed (faster) JSON =====
fload(multiple_urls, query = "name", verbose = TRUE,
      compressed_download = TRUE)

## End(Not run)
```

is_valid_json

simdjson Utilities

Description

simdjson Utilities

Usage

```
is_valid_json(json)
```

```
is_valid_utf8(x)
```

```
fminify(json)
```

Arguments

json	JSON string(s), or raw vectors representing JSON string(s)
x	String(s), or raw vectors representing string(s).

Value

The predicates return a boolean, and `fminify` returns a string

Examples

```
prettified_json <-
  '[
  {
    "b": true,
    "c": null
  },
  {
    "b": [
      [
        1,
        2,
        3
      ],
      [
        4,
        5,
        6
      ]
    ],
    "c": "Q"
  }
]'

example_text <- list(
  valid_json = c(json1 = prettified_json,
                  json2 = '{\n\t"good_json":true\n}'),
  invalid_json = c(bad_json1 = "BAD JSON",
                   bad_json2 = `Encoding<`('"fa\xE7ile"', "latin1")),
  mixed_json = c(na = NA_character_, good_json = '{"good_json":true}',
                 bad_json = `Encoding<`('"fa\xE7ile"', "latin1")),
  good_raw_json = charToRaw('{\n\t"good_json":true\n}'),
  bad_raw_json = charToRaw("JUNK"),
  list_of_raw_json = lapply(
    c(na = NA_character_, good_json = '{"good_json":true}',
      bad_json = `Encoding<`('"fa\xE7ile"', "latin1")),
    charToRaw
  ),
)
```

```

    not_utf8 = `Encoding<-`('"fa\xE7ile"', "latin1")
)

# UTF-8 validation =====
example_text$valid_json
is_valid_utf8(example_text$valid_json)

example_text$invalid_json
is_valid_utf8(example_text$invalid_json)

example_text$mixed_json
is_valid_utf8(example_text$mixed_json)

example_text$good_raw_json
is_valid_utf8(example_text$good_raw_json)

example_text$bad_raw_json
is_valid_utf8(example_text$bad_raw_json)

example_text$list_of_raw_json
is_valid_utf8(example_text$list_of_raw_json)

example_text$not_utf8
is_valid_utf8(example_text$not_utf8)
is_valid_utf8(iconv(example_text$not_utf8, from = "latin1", to = "UTF-8"))

# JSON validation =====
cat(example_text$valid_json[[1L]])
cat(example_text$valid_json[[2L]])
is_valid_json(example_text$valid_json)

example_text$invalid_json
is_valid_json(example_text$invalid_json)

example_text$mixed_json
is_valid_json(example_text$mixed_json)

example_text$good_raw_json
cat(rawToChar(example_text$good_raw_json))
is_valid_json(example_text$good_raw_json)

example_text$bad_raw_json
rawToChar(example_text$bad_raw_json)
is_valid_json(example_text$bad_raw_json)

example_text$list_of_raw_json
lapply(example_text$list_of_raw_json, rawToChar)
is_valid_json(example_text$list_of_raw_json)

example_text$not_utf8
Encoding(example_text$not_utf8)
is_valid_json(example_text$not_utf8)
is_valid_json(iconv(example_text$not_utf8, from = "latin1", to = "UTF-8"))

```

```

# JSON minification =====
cat(example_text$valid_json[[1L]])
cat(example_text$valid_json[[2L]])
fminify(example_text$valid_json)

example_text$invalid_json
fminify(example_text$invalid_json)

example_text$mixed_json
fminify(example_text$mixed_json)

example_text$good_raw_json
cat(rawToChar(example_text$good_raw_json))
fminify(example_text$good_raw_json)

example_text$bad_raw_json
rawToChar(example_text$bad_raw_json)
fminify(example_text$bad_raw_json)

example_text$list_of_raw_json
lapply(example_text$list_of_raw_json, rawToChar)
fminify(example_text$list_of_raw_json)

example_text$not_utf8
Encoding(example_text$not_utf8)
fminify(example_text$not_utf8)
fminify(iconv(example_text$not_utf8, from = "latin1", to = "UTF-8"))

```

parseExample

Simple JSON Parsing Example

Description

Simple JSON Parsing Example

Usage

```
parseExample()
```

Value

Nothing is returned, the function is invoked for its side effect.

This example is adapted from a blogpost announcing an earlier ‘simdjson’ release. It is of interest mostly for the elegance and conciseness of its C++ code rather than for any functionality exported to R.

The function takes no argument and returns nothing.

Examples

```
parseExample()
```

release_json_memory	<i>Release Memory Kept Between Calls</i>
---------------------	--

Description

To parse faster, `fparse()` and `fload()` keep some memory between calls: a buffer holding a copy of the input (as large as the largest document parsed, and released after a call when larger than 64 MiB), and a small cache of short strings. `release_json_memory()` frees this memory now. It is allocated again as needed, so it is always safe to call.

Usage

```
release_json_memory()
```

Value

The number of bytes freed, invisibly.

Examples

```
x <- fparse('{ "a": [1, 2, 3] }')
release_json_memory()
```

validateJSON	<i>Validate a JSON file, fast</i>
--------------	-----------------------------------

Description

By relying on simd-parallel 'simdjson' header-only library JSON files can be parsed very quickly.

Usage

```
validateJSON(jsonfile)
```

Arguments

jsonfile	A character variable with a path and filename
----------	---

Value

A boolean value indicating whether the JSON content was parsed successfully

Examples

```
if (!RcppSimdJson:::unsupportedArchitecture()) {  
  jsonfile <- system.file("jsonexamples", "twitter.json", package="RcppSimdJson")  
  validateJSON(jsonfile)  
}
```

Index

* **package**

RcppSimdJson-package, [2](#)

fload (fparse), [3](#)

fminify (is_valid_json), [8](#)

fparse, [3](#)

is_valid_json, [8](#)

is_valid_utf8 (is_valid_json), [8](#)

parseExample, [11](#)

RcppSimdJson (RcppSimdJson-package), [2](#)

RcppSimdJson-package, [2](#)

release_json_memory, [12](#)

simdjson-utilities (is_valid_json), [8](#)

validateJSON, [12](#)