Package 'caviarpd'

September 25, 2026

Type Package

Title Cluster Analysis via Random Partition Distributions

Version 0.3.25

Description Cluster analysis is performed using pairwise distance information and a random partition distribution. The method is
implemented for two random partition distributions. It draws samples and then obtains and plots clustering estimates.
An implementation of a selection algorithm is provided for the mass parameter of the partition distribution. Since
pairwise distances are the principal input to this procedure, it is most comparable to the hierarchical and k-medoids
clustering methods. The method is Dahl, Andros, Carter (2022+) <doi:10.1002/sam.11602>.

License MIT + file LICENSE | Apache License 2.0

URL https://github.com/dbdahl/caviarpd-package

BugReports https://github.com/dbdahl/caviarpd-package/issues

Depends R (>= 4.3)

Suggests salso (>= 0.3.0)

SystemRequirements Cargo (Rust's package manager), rustc (>= 1.85.1)

Encoding UTF-8

RoxygenNote 7.3.3

Config/Roxido/TemplateVersion 26.09.24.14.30

Config/Roxido/MinCLIVersion 0.8.0

NeedsCompilation yes

Author David B. Dahl [aut, cre] (ORCID:
<https://orcid.org/0000-0002-8173-1547>),
R. Jacob Andros [aut] (ORCID: <https://orcid.org/0000-0002-1289-385X>),
J. Brandon Carter [aut] (ORCID:
<https://orcid.org/0000-0003-1687-0564>),
Authors of the dependency Rust crates [ctb] (see inst/AUTHORS file for
details)

Maintainer David B. Dahl <dahl@stat.byu.edu>

Repository CRAN

Date/Publication 2026-09-25 04:50:20 UTC

Contents

caviarpd 2

Index **4**

`caviarpd` *Cluster Analysis via Random Partition Distributions*

Description

Returns a clustering estimate given pairwise distances using the CaviarPD method.

Usage

```
caviarpd(
  distance,
  nClusters,
  mass = NULL,
  nSamples = 200,
  gridLength = 5,
  loss = "binder",
  temperature = 100,
  similarity = c("exponential", "reciprocal")[1],
  maxNClusters = 0,
  nRuns = 4,
  nCores = nRuns
)
```

Arguments

`distance`	An object of class 'dist' or a pairwise distance matrix.
`nClusters`	A numeric vector that specifies the range for the number of clusters to consider in the search for a clustering estimate.
`mass`	The mass value to use for sampling. If `NULL`, the mass value is found by inverting values from `nClusters`.
`nSamples`	The number of samples drawn per candidate estimate.
`gridLength`	The number of candidate estimates to consider. The final estimate is obtained from `nSamples` $\times$ `gridLength` total samples.
`loss`	The SALSO method (Dahl, Johnson, Müller, 2021) tries to minimize this expected loss when searching the partition space for an optimal estimate. This must be either "binder" or "VI".

`temperature`	A positive number that accentuates or dampens distance between observations.
`similarity`	Either `"exponential"` or `"reciprocal"` to indicate the desired similarity function.
`maxNClusters`	The maximum number of clusters that can be considered by the SALSO method.
`nRuns`	The number of runs of the SALSO algorithm.
`nCores`	The number of CPU cores to use. A value of zero indicates to use all cores on the system.

Details

A range for the number of clusters to be considered is supplied using the `nClusters` argument.

Value

A object of class `salso.estimate`, which provides a clustering estimate (a vector of cluster labels) that can be displayed and plotted.

References

D. B. Dahl, J. Andros, J. B. Carter (2023), Cluster Analysis via Random Partition Distributions, *Statistical Analysis and Data Mining*, doi:10.1002/sam.11602.

D. B. Dahl, D. J. Johnson, and P. Müller (2022), Search Algorithms and Loss Functions for Bayesian Clustering, *Journal of Computational and Graphical Statistics*, 31(4), 1189-1201, doi:10.1080/10618600.2022.2069779. ’

Examples

```
# To reduce load on CRAN servers, limit the number of samples, grid length, and CPU cores.
set.seed(34)
iris.dis <- dist(iris[,-5])
est <- caviarpd(distance=iris.dis, nClusters=c(2,4), nSamples=20, nCores=1)
if ( require("salso") ) {
  summ <- summary(est, orderingMethod=2)
  plot(summ, type="heatmap")
  plot(summ, type="mds")
}
```

Index

caviarpd, 2