

Package ‘gglogger’

October 17, 2026

Type Package

Title Track 'ggplot2' Calls

Version 0.1.9

Description Provides a way to log 'ggplot' component calls, which can be useful for debugging and understanding how 'ggplot' objects are created. The logged calls can be printed, saved, and re-executed to reproduce the original 'ggplot' object.

License MIT + file LICENSE

Imports ggplot2, cli, methods

Suggests rlang, testthat, S7

RoxygenNote 7.3.3

Encoding UTF-8

URL <https://github.com/pwwang/gglogger/>

NeedsCompilation no

Author Panwen Wang [aut, cre] (ORCID: <<https://orcid.org/0000-0002-4614-8970>>)

Maintainer Panwen Wang <pwwang@pwwang.com>

Repository CRAN

Date/Publication 2026-10-17 03:40:02 UTC

Contents

GGLog-class	2
GGLogs-class	2
ggplot	3
print.GGLog	3
print.GGLogs	4
register	4

Index	5
--------------	----------

GGLog-class

GGLog class

Description

The 'GGLog' class is used to store a single ggplot call.

Fields

`code` A string to store the code of the ggplot call.

Methods

`evaluate(envir = parent.frame())` Evaluate the log.
 @param `envir` The environment to evaluate the log in.
`stringify()` Stringify the log.
 @return A string.

GGLogs-class

GGLogs class

Description

The 'GGLogs' class is used to store logs of ggplot calls. Each log is stored as a 'GGLog' object. The object can be accessed using the '\$logs' field from a ggplot object.

Fields

`logs` A list to store the logs.

Methods

`add(log)` Add a log to the list.
 @param `log` A GGLog object.
`evaluate(envir = parent.frame())` Evaluate all logs in the list.
 @param `envir` The environment to evaluate the logs in.
`gen_code(setup = "library(ggplot2)")` Generate code for all logs in the list.
 @param `setup` A string to setup the environment.
 @return A string of code.
`stringify()` Stringify all logs in the list.
 @return A string.

ggplot	<i>Override ggplot function to log calls</i>
--------	--

Description

Override ggplot function to log calls

Usage

```
ggplot(...)
```

Arguments

... Arguments passed to ggplot2::ggplot.

Value

A ggplot object with logged calls.

print.GGLog	<i>Print a GGLog object</i>
-------------	-----------------------------

Description

Print a GGLog object

Usage

```
## S3 method for class 'GGLog'  
print(x, ...)
```

Arguments

x A GGLog object.
... Additional arguments.

Value

Display the logs and invisibly return the logs.

<code>print.GGLogs</code>	<i>Print a GGLogs object</i>
---------------------------	------------------------------

Description

Print a GGLogs object

Usage

```
## S3 method for class 'GGLogs'  
print(x, ...)
```

Arguments

<code>x</code>	A GGLogs object.
<code>...</code>	Additional arguments.

Value

Display the logs and invisibly return the logs.

<code>register</code>	<i>Register a function that returns a ggplot object This is usually implemented by ggplot extensions.</i>
-----------------------	---

Description

Register a function that returns a ggplot object This is usually implemented by ggplot extensions.

Usage

```
register(f, name = NULL)
```

Arguments

<code>f</code>	A function that returns a ggplot object.
<code>name</code>	A string to represent the name of the function.

Value

A function that returns a ggplot object with logged calls.

Index

GGLog (GGLog-class), [2](#)
GGLog-class, [2](#)
GGLogs (GGLogs-class), [2](#)
GGLogs-class, [2](#)
ggplot, [3](#)

print.GGLog, [3](#)
print.GGLogs, [4](#)

register, [4](#)