Package 'healthyR.ai'

August 21, 2026

Title The Machine Learning and AI Modeling Companion to 'healthyR'

Version 0.1.2

Description
Hospital machine learning and ai data analysis workflow tools, modeling, and automations. This library provides many useful tools to review common administrative hospital data. Some of these include predicting length of stay, and readmits. The aim is to provide a simple and consistent verb framework that takes the guesswork out of everything.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.3

URL https://www.spsanderson.com/healthyR.ai/,
https://github.com/spsanderson/healthyR.ai

BugReports https://github.com/spsanderson/healthyR.ai/issues

Imports rlang (>= 0.1.2), yardstick (>= 0.0.8), utils, broom, ggrepel, tibble, dplyr, ggplot2, tidyr, forcats, recipes (>= 1.0.0), purrr, stats, dials, parsnip, tune, workflows

Suggests rmarkdown, knitr, healthyR.data, scales, tidyselect, janitor, timetk, plotly, rsample, kknn, hardhat, uwot, stringr, parallel, parallelly, doParallel, h2o

VignetteBuilder knitr

Depends R (>= 4.1.0)

NeedsCompilation no

Author Steven Sanderson [aut, cre, cph] (ORCID: <https://orcid.org/0009-0006-7661-8247>)

Maintainer Steven Sanderson <spsanderson@gmail.com>

Repository CRAN

Date/Publication 2026-08-21 14:40:33 UTC

Contents

color_blind . . . 3
generate_mesh_data . . . 4
get_juiced_data . . . 5
hai_auto_c50 . . . 7
hai_auto_cubist . . . 8
hai_auto_earth . . . 10
hai_auto_glmnet . . . 12
hai_auto_knn . . . 13
hai_auto_ranger . . . 15
hai_auto_svm_poly . . . 17
hai_auto_svm_rbf . . . 18
hai_auto_wflw_metrics . . . 20
hai_auto_xgboost . . . 21
hai_c50_data_prepper . . . 23
hai_control_chart . . . 24
hai_cubist_data_prepper . . . 25
hai_data_impute . . . 27
hai_data_poly . . . 29
hai_data_scale . . . 31
hai_data_transform . . . 33
hai_data_trig . . . 36
hai_default_classification_metric_set . . . 37
hai_default_regression_metric_set . . . 38
hai_density_hist_plot . . . 39
hai_density_plot . . . 40
hai_density_qq_plot . . . 41
hai_distribution_comparison_tbl . . . 43
hai_earth_data_prepper . . . 45
hai_fourier_augment . . . 46
hai_fourier_discrete_augment . . . 48
hai_fourier_discrete_vec . . . 49
hai_fourier_vec . . . 51
hai_get_density_data_tbl . . . 53
hai_get_dist_data_tbl . . . 54
hai_glmnet_data_prepper . . . 55
hai_histogram_facet_plot . . . 56
hai_hyperbolic_augment . . . 57
hai_hyperbolic_vec . . . 59
hai_kmeans_automl . . . 60
hai_kmeans_automl_predict . . . 62
hai_kmeans_mapped_tbl . . . 63
hai_kmeans_obj . . . 64
hai_kmeans_scree_data_tbl . . . 66
hai_kmeans_scree_plt . . . 67
hai_kmeans_tidy_tbl . . . 68
hai_kmeans_user_item_tbl . . . 70

hai_knn_data_prepper . . . 71
hai_kurtosis_vec . . . 72
hai_polynomial_augment . . . 73
hai_ranger_data_prepper . . . 74
hai_range_statistic . . . 76
hai_scale_color_colorblind . . . 76
hai_scale_fill_colorblind . . . 77
hai_scale_zero_one_augment . . . 78
hai_scale_zero_one_vec . . . 79
hai_scale_zscore_augment . . . 80
hai_scale_zscore_vec . . . 81
hai_skewed_features . . . 82
hai_skewness_vec . . . 83
hai_svm_poly_data_prepper . . . 84
hai_svm_rbf_data_prepper . . . 85
hai_umap_list . . . 86
hai_umap_plot . . . 88
hai_winsorized_move_augment . . . 89
hai_winsorized_move_vec . . . 90
hai_winsorized_truncate_augment . . . 92
hai_winsorized_truncate_vec . . . 93
hai_xgboost_data_prepper . . . 94
pca_your_recipe . . . 95
step_hai_fourier . . . 97
step_hai_fourier_discrete . . . 99
step_hai_hyperbolic . . . 101
step_hai_scale_zero_one . . . 103
step_hai_scale_zscore . . . 105
step_hai_winsorized_move . . . 107
step_hai_winsorized_truncate . . . 109

Index **112**

`color_blind` *Provide Colorblind Compliant Colors*

Description

8 Hex RGB color definitions suitable for charts for colorblind people.

Usage

```
color_blind()
```

Details

This function is used in others in order to help render plots for those that are color blind.

Value

A vector of 8 Hex RGB definitions.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Color_Blind: `hai_scale_color_colorblind()`, `hai_scale_fill_colorblind()`

Examples

```
color_blind()
```

`generate_mesh_data` *Generate Mesh Data*

Description

This function creates a square mesh by sampling nodes uniformly on a square and then connecting these nodes with edges. The nodes are distributed based on the provided side length and number of segments. Horizontal, vertical, and diagonal edges are generated to fully connect the mesh. The function returns a list containing the nodes and edges, along with data frames and a ggplot object for visualization.

Usage

```
generate_mesh_data(.side_length = 1, .n_seg = 1)
```

Arguments

`.side_length`	A single numeric value representing the side length of the square.
`.n_seg`	A positive integer representing the number of segments along each side of the square.

Details

This function generates a mesh of nodes and edges based on the provided side length and number of segments.

This function creates a square mesh of nodes and edges, where the nodes are sampled uniformly on a square. The edges are generated to connect the nodes horizontally, vertically, and diagonally.

Value

A list containing:

nodes A matrix with coordinates of the nodes.

edges A list of edges connecting the nodes.

nodes_df A data frame of nodes for ggplot.

edges_df A data frame of edges for ggplot.

plot A ggplot object visualizing the nodes and edges.

Additionally, the list contains attributes:

side_length The side length used to generate the mesh.

n_seg The number of segments used to generate the mesh.

nodes_df_dim Dimensions of the nodes data frame.

edges_df_dim Dimensions of the edges data frame.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Data Generation: `get_juiced_data()`

Examples

```
generate_mesh_data(1, 1)
generate_mesh_data(1, 2)
```

---

get_juiced_data *Get the Juiced Data*

Description

This is a simple function that will get the juiced data from a recipe.

Usage

```
get_juiced_data(.recipe_object)
```

Arguments

`.recipe_object` The recipe object you want to pass.

Details

Instead of typing out something like: `recipe_object |> prep() |> juice() |> glimpse()`

Value

A tibble of the prepped and juiced data from the given recipe

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Data Generation: `generate_mesh_data()`

Examples

```
suppressPackageStartupMessages(library(timetk))
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(purrr))
suppressPackageStartupMessages(library(healthyR.data))
suppressPackageStartupMessages(library(rsample))
suppressPackageStartupMessages(library(recipes))

data_tbl <- healthyR_data |>
  select(visit_end_date_time) |>
  summarise_by_time(
    .date_var = visit_end_date_time,
    .by       = "month",
    value     = n()
  ) |>
  set_names("date_col", "value") |>
  filter_by_time(
    .date_var = date_col,
    .start_date = "2013",
    .end_date = "2020"
  )

splits <- initial_split(data = data_tbl, prop = 0.8)

rec_obj <- recipe(value ~ ., training(splits))

get_juiced_data(rec_obj)
```

`hai_auto_c50` *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_c50(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "f_meas",
  .model_type = "classification"
)
```

Arguments

`.data`	The data being passed to the function. The time-series object.
`.rec_obj`	This is the recipe object you want to use. You can use `hai_c50_data_prepper()` an automatic recipe_object.
`.splits_obj`	NULL is the default, when NULL then one will be created.
`.rsamp_obj`	NULL is the default, when NULL then one will be created. It will default to creating an `rsample::mc_cv()` object.
`.tune`	Default is TRUE, this will create a tuning grid and tuned workflow
`.grid_size`	Default is 10
`.num_cores`	Default is 1
`.best_metric`	Default is "f_meas". You can choose a metric depending on the model_type used. If `regression` then see `hai_default_regression_metric_set()`, if `classification` then see `hai_default_classification_metric_set()`.
`.model_type`	Default is `classification`, can also be `regression`.

Details

This uses the `parsnip::boost_tree()` with the `engine` set to `C5.0`

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Boiler_Plate: hai_auto_cubist(), hai_auto_earth(), hai_auto_glmnet(), hai_auto_knn(), hai_auto_ranger(), hai_auto_svm_poly(), hai_auto_svm_rbf(), hai_auto_wflw_metrics(), hai_auto_xgboost()

Other C5.0: hai_c50_data_prepper()

Examples

```
## Not run:
data <- iris

rec_obj <- hai_c50_data_prepper(data, Species ~ .)

auto_c50 <- hai_auto_c50(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas",
  .model_type = "classification"
)

auto_c50$recipe_info

## End(Not run)
```

---

hai_auto_cubist *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_cubist(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "rmse"
)
```

Arguments

.data	The data being passed to the function. The time-series object.
.rec_obj	This is the recipe object you want to use. You can use hai_cubist_data_prepper() an automatic recipe_object.
.splits_obj	NULL is the default, when NULL then one will be created.
.rsamp_obj	NULL is the default, when NULL then one will be created. It will default to creating an rsample::mc_cv() object.
.tune	Default is TRUE, this will create a tuning grid and tuned workflow
.grid_size	Default is 10
.num_cores	Default is 1
.best_metric	Default is "rmse". The only .model_type you can use with Cubist is regression so use hai_default_regression_metric_set() to get the available metrics. Because of this the .model_type parameter is omitted from this function.

Details

This uses the parsnip::cubist_rules() with the engine set to cubist

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Boiler_Plate: hai_auto_c50(), hai_auto_earth(), hai_auto_glmnet(), hai_auto_knn(), hai_auto_ranger(), hai_auto_svm_poly(), hai_auto_svm_rbf(), hai_auto_wflw_metrics(), hai_auto_xgboost()

Other cubist: hai_cubist_data_prepper()

Examples

```
## Not run:
data <- mtcars

rec_obj <- hai_cubist_data_prepper(data, mpg ~ .)

auto_cube <- hai_auto_cubist(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "rmse"
)

auto_cube$recipe_info

## End(Not run)
```

`hai_auto_earth` *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_earth(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "f_meas",
  .model_type = "classification"
)
```

Arguments

.data	The data being passed to the function. The time-series object.
.rec_obj	This is the recipe object you want to use. You can use hai_earth_data_prepper() an automatic recipe_object.
.splits_obj	NULL is the default, when NULL then one will be created.
.rsamp_obj	NULL is the default, when NULL then one will be created. It will default to creating an rsample::mc_cv() object.
.tune	Default is TRUE, this will create a tuning grid and tuned workflow
.grid_size	Default is 10
.num_cores	Default is 1
.best_metric	Default is "f_meas". You can choose a metric depending on the model_type used. If regression then see hai_default_regression_metric_set(), if classification then see hai_default_classification_metric_set().
.model_type	Default is classification, can also be regression.

Details

This uses the parsnip::mars() with the engine set to earth

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

http://uc-r.github.io/mars

Other Boiler_Plate: hai_auto_c50(), hai_auto_cubist(), hai_auto_glmnet(), hai_auto_knn(), hai_auto_ranger(), hai_auto_svm_poly(), hai_auto_svm_rbf(), hai_auto_wflw_metrics(), hai_auto_xgboost()

Other Earth: hai_earth_data_prepper()

Examples

```
## Not run:
data <- iris

rec_obj <- hai_earth_data_prepper(data, Species ~ .)

auto_earth <- hai_auto_earth(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas",
  .model_type = "classification"
```

```
)

auto_earth$recipe_info

## End(Not run)
```

`hai_auto_glmnet` *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_glmnet(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "f_meas",
  .model_type = "classification"
)
```

Arguments

`.data`	The data being passed to the function. The time-series object.
`.rec_obj`	This is the recipe object you want to use. You can use `hai_glmnet_data_prepper()` an automatic recipe_object.
`.splits_obj`	NULL is the default, when NULL then one will be created.
`.rsamp_obj`	NULL is the default, when NULL then one will be created. It will default to creating an `rsample::mc_cv()` object.
`.tune`	Default is TRUE, this will create a tuning grid and tuned workflow
`.grid_size`	Default is 10
`.num_cores`	Default is 1
`.best_metric`	Default is "f_meas". You can choose a metric depending on the model_type used. If `regression` then see `hai_default_regression_metric_set()`, if `classification` then see `hai_default_classification_metric_set()`.
`.model_type`	Default is `classification`, can also be `regression`.

Details

This uses the `parsnip::multinom_reg()` with the `engine` set to `glmnet`

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Boiler_Plate: `hai_auto_c50()`, `hai_auto_cubist()`, `hai_auto_earth()`, `hai_auto_knn()`, `hai_auto_ranger()`, `hai_auto_svm_poly()`, `hai_auto_svm_rbf()`, `hai_auto_wflw_metrics()`, `hai_auto_xgboost()`

Examples

```
## Not run:
data <- iris

rec_obj <- hai_glmnet_data_prepper(data, Species ~ .)

auto_glm <- hai_auto_glmnet(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas",
  .model_type = "classification"
)

auto_glm$recipe_info

## End(Not run)
```

`hai_auto_knn` *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_knn(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "rmse",
  .model_type = "regression"
)
```

Arguments

.data	The data being passed to the function. The time-series object.
.rec_obj	This is the recipe object you want to use. You can use hai_knn_data_prepper() an automatic recipe_object.
.splits_obj	NULL is the default, when NULL then one will be created.
.rsamp_obj	NULL is the default, when NULL then one will be created. It will default to creating an rsample::mc_cv() object.
.tune	Default is TRUE, this will create a tuning grid and tuned workflow
.grid_size	Default is 10
.num_cores	Default is 1
.best_metric	Default is "rmse". You can choose a metric depending on the model_type used. If regression then see hai_default_regression_metric_set(), if classification then see hai_default_classification_metric_set().
.model_type	Default is regression, can also be classification.

Details

This uses the parsnip::nearest_neighbor() with the engine set to kknn

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Boiler_Plate: hai_auto_c50(), hai_auto_cubist(), hai_auto_earth(), hai_auto_glmnet(), hai_auto_ranger(), hai_auto_svm_poly(), hai_auto_svm_rbf(), hai_auto_wflw_metrics(), hai_auto_xgboost()

Examples

```
## Not run:
data <- iris

rec_obj <- hai_knn_data_prepper(data, Species ~ .)

auto_knn <- hai_auto_knn(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas",
  .model_type = "classification"
)

auto_knn$recipe_info

## End(Not run)
```

---

hai_auto_ranger *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_ranger(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "f_meas",
  .model_type = "classification"
)
```

Arguments

.data	The data being passed to the function. The time-series object.
.rec_obj	This is the recipe object you want to use. You can use hai_ranger_data_prepper() an automatic recipe_object.
.splits_obj	NULL is the default, when NULL then one will be created.
.rsamp_obj	NULL is the default, when NULL then one will be created. It will default to creating an rsample::mc_cv() object.
.tune	Default is TRUE, this will create a tuning grid and tuned workflow
.grid_size	Default is 10
.num_cores	Default is 1
.best_metric	Default is "f_meas". You can choose a metric depending on the model_type used. If regression then see hai_default_regression_metric_set(), if classification then see hai_default_classification_metric_set().
.model_type	Default is classification, can also be regression.

Details

This uses the parsnip::rand_forest() with the engine set to kernlab

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/rand_forest.html

Other Boiler_Plate: hai_auto_c50(), hai_auto_cubist(), hai_auto_earth(), hai_auto_glmnet(), hai_auto_knn(), hai_auto_svm_poly(), hai_auto_svm_rbf(), hai_auto_wflw_metrics(), hai_auto_xgboost()

Other Ranger: hai_ranger_data_prepper()

Examples

```
## Not run:
data <- iris

rec_obj <- hai_ranger_data_prepper(data, Species ~ .)

auto_ranger <- hai_auto_ranger(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas"
)
```

```
auto_ranger$recipe_info

## End(Not run)
```

`hai_auto_svm_poly` *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_svm_poly(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "f_meas",
  .model_type = "classification"
)
```

Arguments

`.data`	The data being passed to the function. The time-series object.
`.rec_obj`	This is the recipe object you want to use. You can use `hai_svm_poly_data_prepper()` an automatic recipe_object.
`.splits_obj`	NULL is the default, when NULL then one will be created.
`.rsamp_obj`	NULL is the default, when NULL then one will be created. It will default to creating an `rsample::mc_cv()` object.
`.tune`	Default is TRUE, this will create a tuning grid and tuned workflow
`.grid_size`	Default is 10
`.num_cores`	Default is 1
`.best_metric`	Default is "f_meas". You can choose a metric depending on the model_type used. If `regression` then see `hai_default_regression_metric_set()`, if `classification` then see `hai_default_classification_metric_set()`.
`.model_type`	Default is `classification`, can also be `regression`.

Details

This uses the `parsnip::svm_poly()` with the `engine` set to `kernlab`

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/svm_poly.html

Other Boiler_Plate: `hai_auto_c50()`, `hai_auto_cubist()`, `hai_auto_earth()`, `hai_auto_glmnet()`, `hai_auto_knn()`, `hai_auto_ranger()`, `hai_auto_svm_rbf()`, `hai_auto_wflw_metrics()`, `hai_auto_xgboost()`

Other SVM_Poly: `hai_svm_poly_data_prepper()`

Examples

```
## Not run:
data <- iris

rec_obj <- hai_svm_poly_data_prepper(data, Species ~ .)

auto_svm_poly <- hai_auto_svm_poly(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas"
)

auto_svm_poly$recipe_info

## End(Not run)
```

---

hai_auto_svm_rbf *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_svm_rbf(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "f_meas",
  .model_type = "classification"
)
```

Arguments

.data	The data being passed to the function. The time-series object.
.rec_obj	This is the recipe object you want to use. You can use hai_svm_rbf_data_prepper() an automatic recipe_object.
.splits_obj	NULL is the default, when NULL then one will be created.
.rsamp_obj	NULL is the default, when NULL then one will be created. It will default to creating an rsample::mc_cv() object.
.tune	Default is TRUE, this will create a tuning grid and tuned workflow
.grid_size	Default is 10
.num_cores	Default is 1
.best_metric	Default is "f_meas". You can choose a metric depending on the model_type used. If regression then see hai_default_regression_metric_set(), if classification then see hai_default_classification_metric_set().
.model_type	Default is classification, can also be regression.

Details

This uses the parsnip::svm_rbf() with the engine set to kernlab

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/svm_rbf.html

Other Boiler_Plate: hai_auto_c50(), hai_auto_cubist(), hai_auto_earth(), hai_auto_glmnet(), hai_auto_knn(), hai_auto_ranger(), hai_auto_svm_poly(), hai_auto_wflw_metrics(), hai_auto_xgboost()

Other SVM_RBF: hai_svm_rbf_data_prepper()

Examples

```
## Not run:
data <- iris

rec_obj <- hai_svm_rbf_data_prepper(data, Species ~ .)

auto_rbf <- hai_auto_svm_rbf(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas"
)

auto_rbf$recipe_info

## End(Not run)
```

---

hai_auto_wflw_metrics *Collect Metrics from Boilerplat Workflows*

Description

This function will extract the metrics from the hai_auto_ boilerplate functions.

Usage

```
hai_auto_wflw_metrics(.data)
```

Arguments

.data	The output of the hai_auto_ boilerplate function in it's entirety.

Details

This function will extract the metrics from the hai_auto_ boilerplate functions. This function looks for a specific attribute from the hai_auto_ functions so that it will extract the tuned_results from the tuning process if it has indeed been tuned.

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Boiler_Plate: hai_auto_c50(), hai_auto_cubist(), hai_auto_earth(), hai_auto_glmnet(), hai_auto_knn(), hai_auto_ranger(), hai_auto_svm_poly(), hai_auto_svm_rbf(), hai_auto_xgboost()

Examples

```
## Not run:
data <- iris

rec_obj <- hai_knn_data_prepper(data, Species ~ .)

auto_knn <- hai_auto_knn(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas",
  .model_type = "classification",
  .grid_size = 2,
  .num_cores = 4
)

hai_auto_wflw_metrics(auto_knn)

## End(Not run)
```

---

hai_auto_xgboost *Boilerplate Workflow*

Description

This is a boilerplate function to create automatically the following:

- recipe
- model specification
- workflow
- tuned model (grid ect)

Usage

```
hai_auto_xgboost(
  .data,
  .rec_obj,
  .splits_obj = NULL,
  .rsamp_obj = NULL,
  .tune = TRUE,
  .grid_size = 10,
  .num_cores = 1,
  .best_metric = "f_meas",
  .model_type = "classification"
)
```

Arguments

.data	The data being passed to the function. The time-series object.
.rec_obj	This is the recipe object you want to use. You can use hai_xgboost_data_prepper() an automatic recipe_object.
.splits_obj	NULL is the default, when NULL then one will be created.
.rsamp_obj	NULL is the default, when NULL then one will be created. It will default to creating an rsample::mc_cv() object.
.tune	Default is TRUE, this will create a tuning grid and tuned workflow
.grid_size	Default is 10
.num_cores	Default is 1
.best_metric	Default is "f_meas". You can choose a metric depending on the model_type used. If regression then see hai_default_regression_metric_set(), if classification then see hai_default_classification_metric_set().
.model_type	Default is classification, can also be regression.

Details

This uses the parsnip::boost_tree() with the engine set to xgboost

Value

A list

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/details_boost_tree_xgboost.html

Other Boiler_Plate: hai_auto_c50(), hai_auto_cubist(), hai_auto_earth(), hai_auto_glmnet(), hai_auto_knn(), hai_auto_ranger(), hai_auto_svm_poly(), hai_auto_svm_rbf(), hai_auto_wflw_metrics()

Examples

```
## Not run:
data <- iris

rec_obj <- hai_xgboost_data_prepper(data, Species ~ .)

auto_xgb <- hai_auto_xgboost(
  .data = data,
  .rec_obj = rec_obj,
  .best_metric = "f_meas"
)

auto_xgb$recipe_info
```

```
## End(Not run)
```

`hai_c50_data_prepper` *Prep Data for C5.0 - Recipe*

Description

Automatically prep a data.frame/tibble for use in the C5.0 algorithm.

Usage

```
hai_c50_data_prepper(.data, .recipe_formula)
```

Arguments

`.data`	The data that you are passing to the function. Can be any type of data that is accepted by the `data` parameter of the `recipes::recipe()` function.
`.recipe_formula`	The formula that is going to be passed. For example if you are using the `iris` data then the formula would most likely be something like `Species ~ .`

Details

This function will automatically prep your data.frame/tibble for use in the C5.0 algorithm. The C5.0 algorithm is a lazy learning classification algorithm. It expects data to be presented in a certain fashion.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://www.rulequest.com/see5-unix.html

Other Preprocessor: `hai_cubist_data_prepper()`, `hai_earth_data_prepper()`, `hai_glmnet_data_prepper()`, `hai_knn_data_prepper()`, `hai_ranger_data_prepper()`, `hai_svm_poly_data_prepper()`, `hai_svm_rbf_data_prepper()`, `hai_xgboost_data_prepper()`

Other C5.0: `hai_auto_c50()`

Examples

```
library(ggplot2)
library(tibble)

Titanic <- as_tibble(Titanic)

hai_c50_data_prepper(.data = Titanic, .recipe_formula = Survived ~ .)
rec_obj <- hai_c50_data_prepper(Titanic, Survived ~ .)
get_juiced_data(rec_obj)
```

`hai_control_chart` *Create a control chart*

Description

Create a control chart, aka Shewhart chart: https://en.wikipedia.org/wiki/Control_chart.

Usage

```
hai_control_chart(
  .data,
  .value_col,
  .x_col,
  .center_line = mean,
  .std_dev = 3,
  .plt_title = NULL,
  .plt_catpion = NULL,
  .plt_font_size = 11,
  .print_plot = TRUE
)
```

Arguments

`.data`	data frame or a path to a csv file that will be read in
`.value_col`	variable of interest mapped to y-axis (quoted, ie as a string)
`.x_col`	variable to go on the x-axis, often a time variable. If unspecified row indices will be used (quoted)
`.center_line`	Function used to calculate central tendency. Defaults to mean
`.std_dev`	Number of standard deviations above and below the central tendency to call a point influenced by "special cause variation." Defaults to 3
`.plt_title`	Plot title
`.plt_catpion`	Plot caption
`.plt_font_size`	Font size; text elements will be scaled to this
`.print_plot`	Print the plot? Default = TRUE. Set to FALSE if you want to assign the plot to a variable for further modification, as in the last example.

Details

Control charts, also known as Shewhart charts (after Walter A. Shewhart) or process-behavior charts, are a statistical process control tool used to determine if a manufacturing or business process is in a state of control. It is more appropriate to say that the control charts are the graphical device for Statistical Process Monitoring (SPM). Traditional control charts are mostly designed to monitor process parameters when underlying form of the process distributions are known. However, more advanced techniques are available in the 21st century where incoming data streaming can-be monitored even without any knowledge of the underlying process distributions. Distribution-free control charts are becoming increasingly popular.

Value

Generally called for the side effect of printing the control chart. Invisibly, returns a ggplot object for further customization.

Author(s)

Steven P. Sanderson II, MPH

Examples

```
data_tbl <- tibble::tibble(
  day = sample(
    c("Monday", "Tuesday", "Wednesday", "Thursday", "Friday"),
    100, TRUE
  ),
  person = sample(c("Tom", "Jane", "Alex"), 100, TRUE),
  count = rbinom(100, 20, ifelse(day == "Friday", .5, .2)),
  date = Sys.Date() - sample.int(100)
)

hai_control_chart(.data = data_tbl, .value_col = count, .x_col = date)

# In addition to printing or writing the plot to file, hai_control_chart
# returns the plot as a ggplot2 object, which you can then further customize

library(ggplot2)
my_chart <- hai_control_chart(data_tbl, count, date)
my_chart +
  ylab("Number of Adverse Events") +
  scale_x_date(name = "Week of ... ", date_breaks = "week") +
  theme(axis.text.x = element_text(angle = -90, vjust = 0.5, hjust = 1))
```

`hai_cubist_data_prepper`

Prep Data for Cubist - Recipe

Description

Automatically prep a data.frame/tibble for use in the cubist algorithm.

Usage

```
hai_cubist_data_prepper(.data, .recipe_formula)
```

Arguments

.data	The data that you are passing to the function. Can be any type of data that is accepted by the data parameter of the recipes::reciep() function.
.recipe_formula	The formula that is going to be passed. For example if you are using the diamonds data then the formula would most likely be something like price ~ .

Details

This function will automatically prep your data.frame/tibble for use in the cubist algorithm. The cubist algorithm is for regression only.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://rulequest.com/cubist-info.html

Other Preprocessor: hai_c50_data_prepper(), hai_earth_data_prepper(), hai_glmnet_data_prepper(), hai_knn_data_prepper(), hai_ranger_data_prepper(), hai_svm_poly_data_prepper(), hai_svm_rbf_data_prepp
hai_xgboost_data_prepper()

Other cubist: hai_auto_cubist()

Examples

```
library(ggplot2)

hai_cubist_data_prepper(.data = diamonds, .recipe_formula = price ~ .)
rec_obj <- hai_cubist_data_prepper(diamonds, price ~ .)
get_juiced_data(rec_obj)
```

`hai_data_impute` *Data Preprocessor - Imputation*

Description

Takes in a recipe and will impute missing values using a selected recipe. To call the recipe use a quoted argument like "median" or "bagged".

Usage

```
hai_data_impute(
  .recipe_object = NULL,
  ...,
  .seed_value = 123,
  .type_of_imputation = "mean",
  .number_of_trees = 25,
  .neighbors = 5,
  .mean_trim = 0,
  .roll_statistic,
  .roll_window = 5
)
```

Arguments

`.recipe_object`	The data that you want to process
`...`	One or more selector functions to choose variables to be imputed. When used with imp_vars, these dots indicate which variables are used to predict the missing data in each variable. See selections() for more details
`.seed_value`	To make results reproducible, set the seed.
`.type_of_imputation`	This is a quoted argument and can be one of the following: • "bagged" • "knn" • "linear" • "lower" • "mean" • "median" • "mode" • "roll"
`.number_of_trees`	This is used for the `recipes::step_impute_bag()` trees parameter. This should be an integer.
`.neighbors`	This should be filled in with an integer value if `.type_of_imputation` selected is "knn".

`.mean_trim` This should be filled in with a fraction if `.type_of_imputation` selected is "mean".

`.roll_statistic` This should be filled in with a single unquoted function that takes with it a single argument such as mean. This should be filled in if `.type_of_imputation` selected is "roll".

`.roll_window` This should be filled in with an integer value if `.type_of_imputation` selected is "roll".

Details

This function will get your data ready for processing with many types of ml/ai models.

This is intended to be used inside of the data processor and therefore is an internal function. This documentation exists to explain the process and help the user understand the parameters that can be set in the pre-processor function.

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://recipes.tidymodels.org/reference/index.html#section-step-functions-imputation/

step_impute_bag

recipes::step_impute_bag()

https://recipes.tidymodels.org/reference/step_impute_bag.html

step_impute_knn

recipes::step_impute_knn()

https://recipes.tidymodels.org/reference/step_impute_knn.html

step_impute_linear

recipes::step_impute_linear()

https://recipes.tidymodels.org/reference/step_impute_linear.html

step_impute_lower

recipes::step_impute_lower()

https://recipes.tidymodels.org/reference/step_impute_lower.html

step_impute_mean

recipes::step_impute_mean()

https://recipes.tidymodels.org/reference/step_impute_mean.html

step_impute_median

recipes::step_impute_median()

https://recipes.tidymodels.org/reference/step_impute_median.html

step_impute_mode

recipes::step_impute_mode()

https://recipes.tidymodels.org/reference/step_impute_mode.html

step_impute_roll

recipes::step_impute_roll()

https://recipes.tidymodels.org/reference/step_impute_roll.html

Other Data Recipes: hai_data_poly(), hai_data_scale(), hai_data_transform(), hai_data_trig(), pca_your_recipe()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

date_seq <- seq.Date(from = as.Date("2013-01-01"), length.out = 100, by = "month")
val_seq <- rep(c(rnorm(9), NA), times = 10)
df_tbl <- tibble(
  date_col = date_seq,
  value    = val_seq
)

rec_obj <- recipe(value ~ ., df_tbl)

hai_data_impute(
  .recipe_object = rec_obj,
  value,
  .type_of_imputation = "roll",
  .roll_statistic = median
)$new_rec_obj |>
  get_juiced_data()
```

---

hai_data_poly *Data Preprocessor - Polynomial Function*

Description

Takes in a recipe and will scale values using a selected recipe.

Usage

```
hai_data_poly(.recipe_object = NULL, ..., .p_degree = 2)
```

Arguments

.recipe_object	The data that you want to process
...	One or more selector functions to choose variables to be imputed. When used with imp_vars, these dots indicate which variables are used to predict the missing data in each variable. See selections() for more details
.p_degree	The polynomial degree, an integer.

Details

This function will get your data ready for processing with many types of ml/ai models.

This is intended to be used inside of the data processor and therefore is an internal function. This documentation exists to explain the process and help the user understand the parameters that can be set in the pre-processor function.

recipes::step_poly()

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://recipes.tidymodels.org/reference/step_poly.html

Other Data Recipes: hai_data_impute(), hai_data_scale(), hai_data_transform(), hai_data_trig(), pca_your_recipe()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

date_seq <- seq.Date(from = as.Date("2013-01-01"), length.out = 100, by = "month")
val_seq <- rep(rnorm(10, mean = 6, sd = 2), times = 10)
df_tbl <- tibble(
  date_col = date_seq,
  value    = val_seq
)

rec_obj <- recipe(value ~ ., df_tbl)

hai_data_poly(
  .recipe_object = rec_obj,
  value
)$new_rec_obj |>
  get_juiced_data()
```

hai_data_scale *Data Preprocessor - Scale/Normalize*

Description

Takes in a recipe and will scale values using a selected recipe. To call the recipe use a quoted argument like "scale" or "normalize".

Usage

```
hai_data_scale(
  .recipe_object = NULL,
  ...,
  .type_of_scale = "center",
  .range_min = 0,
  .range_max = 1,
  .scale_factor = 1
)
```

Arguments

.recipe_object	The data that you want to process
...	One or more selector functions to choose variables to be imputed. When used with imp_vars, these dots indicate which variables are used to predict the missing data in each variable. See selections() for more details
.type_of_scale	This is a quoted argument and can be one of the following: • "center" • "normalize" • "range" • "scale"
.range_min	A single numeric value for the smallest value in the range. This defaults to 0.
.range_max	A single numeric value for the largeest value in the range. This defaults to 1.
.scale_factor	A numeric value of either 1 or 2 that scales the numeric inputs by one or two standard deviations. By dividing by two standard deviations, the coefficients attached to continuous predictors can be interpreted the same way as with binary inputs. Defaults to 1. More in reference below.

Details

This function will get your data ready for processing with many types of ml/ai models.

This is intended to be used inside of the data processor and therefore is an internal function. This documentation exists to explain the process and help the user understand the parameters that can be set in the pre-processor function.

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

References

Gelman, A. (2007) "Scaling regression inputs by dividing by two standard deviations." Unpublished. Source: https://sites.stat.columbia.edu/gelman/research/unpublished/standardizing.pdf.

See Also

https://recipes.tidymodels.org/reference/index.html#section-step-functions-normalization

step_center

recipes::step_center()

https://recipes.tidymodels.org/reference/step_center.html

step_normalize

recipes::step_normalize()

https://recipes.tidymodels.org/reference/step_normalize.html

step_range

recipes::step_range()

https://recipes.tidymodels.org/reference/step_range.html

step_scale

recipes::step_scale()

https://recipes.tidymodels.org/reference/step_scale.html

Other Data Recipes: hai_data_impute(), hai_data_poly(), hai_data_transform(), hai_data_trig(), pca_your_recipe()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

date_seq <- seq.Date(from = as.Date("2013-01-01"), length.out = 100, by = "month")
val_seq <- rep(rnorm(10, mean = 6, sd = 2), times = 10)
df_tbl <- tibble(
  date_col = date_seq,
  value    = val_seq
)

rec_obj <- recipe(value ~ ., df_tbl)

hai_data_scale(
```

```
  .recipe_object = rec_obj,
  value,
  .type_of_scale = "center"
)$new_rec_obj |>
  get_juiced_data()
```

`hai_data_transform` *Data Preprocessor - Transformation Functions*

Description

Takes in a recipe and will perform the desired transformation on the selected varialbe(s) using a selected recipe. To call the desired transformation recipe use a quoted argument like "boxcos", "bs" etc.

Usage

```
hai_data_transform(
  .recipe_object = NULL,
  ...,
  .type_of_scale = "log",
  .bc_limits = c(-5, 5),
  .bc_num_unique = 5,
  .bs_deg_free = NULL,
  .bs_degree = 3,
  .log_base = exp(1),
  .log_offset = 0,
  .logit_offset = 0,
  .ns_deg_free = 2,
  .rel_shift = 0,
  .rel_reverse = FALSE,
  .rel_smooth = FALSE,
  .yj_limits = c(-5, 5),
  .yj_num_unique = 5
)
```

Arguments

`.recipe_object`	The data that you want to process
`...`	One or more selector functions to choose variables to be imputed. When used with imp_vars, these dots indicate which variables are used to predict the missing data in each variable. See selections() for more details
`.type_of_scale`	This is a quoted argument and can be one of the following: • "boxcox" • "bs"

- "log"
- "logit"
- "ns"
- "relu"
- "sqrt"
- "yeojohnson

`.bc_limits` A length 2 numeric vector defining the range to compute the transformation parameter lambda.

`.bc_num_unique` An integer to specify minimum required unique values to evaluate for a transformation

`.bs_deg_free` The degrees of freedom for the spline. As the degrees of freedom for a spline increase, more flexible and complex curves can be generated. When a single degree of freedom is used, the result is a rescaled version of the original data.

`.bs_degree` Degree of polynomial spline (integer).

`.log_base` A numberic value for the base.

`.log_offset` An optional value to add to the data prior to logging (to avoid log(0))

`.logit_offset` A numberic value to modify values ofthe columns that are either one or zero. They are modifed to be `x - offset` or `offset` respectively.

`.ns_deg_free` The degrees of freedom for the natural spline. As the degrees of freedom for a natural spline increase, more flexible and complex curves can be generated. When a single degree of freedom is used, the result is a rescaled version of the original data.

`.rel_shift` A numeric value dictating a translation to apply to the data.

`.rel_reverse` A logical to indicate if theleft hinge should be used as opposed to the right hinge.

`.rel_smooth` A logical indicating if hte softplus function, a smooth approximation to the rectified linear transformation, should be used.

`.yj_limits` A length 2 numeric vector defining the range to compute the transformation parameter lambda.

`.yj_num_unique` An integer where data that have less possible values will not be evaluated for a transformation.

Details

This function will get your data ready for processing with many types of ml/ai models.

This is intended to be used inside of the data processor and therefore is an internal function. This documentation exists to explain the process and help the user understand the parameters that can be set in the pre-processor function.

`recipes::step_BoxCox()`

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://recipes.tidymodels.org/reference/step_BoxCox.html

recipes::step_bs()

https://recipes.tidymodels.org/reference/step_bs.html

recipes::step_log()

https://recipes.tidymodels.org/reference/step_log.html

recipes::step_logit()

https://recipes.tidymodels.org/reference/step_logit.html

recipes::step_ns()

https://recipes.tidymodels.org/reference/step_ns.html

recipes::step_relu()

https://recipes.tidymodels.org/reference/step_relu.html

recipes::step_sqrt()

https://recipes.tidymodels.org/reference/step_sqrt.html

recipes::step_YeoJohnson()

https://recipes.tidymodels.org/reference/step_YeoJohnson.html

Other Data Recipes: hai_data_impute(), hai_data_poly(), hai_data_scale(), hai_data_trig(), pca_your_recipe()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

date_seq <- seq.Date(from = as.Date("2013-01-01"), length.out = 100, by = "month")
val_seq <- rep(rnorm(10, mean = 6, sd = 2), times = 10)
df_tbl <- tibble(
  date_col = date_seq,
  value    = val_seq
)

rec_obj <- recipe(value ~ ., df_tbl)

hai_data_transform(
  .recipe_object = rec_obj,
  value,
  .type_of_scale = "log"
)$new_rec_obj |>
  get_juiced_data()
```

`hai_data_trig` *Data Preprocessor - Trigonometric Functions*

Description

Takes in a recipe and will scale values using a selected recipe. To call the recipe use a quoted argument like "sinh", "cosh" or "tanh".

Usage

```
hai_data_trig(
  .recipe_object = NULL,
  ...,
  .type_of_scale = "sinh",
  .inverse = FALSE
)
```

Arguments

`.recipe_object`	The data that you want to process
`...`	One or more selector functions to choose variables to be imputed. When used with imp_vars, these dots indicate which variables are used to predict the missing data in each variable. See selections() for more details
`.type_of_scale`	This is a quoted argument and can be one of the following: • "sinh" • "cosh" • "tanh"
`.inverse`	A logical: should the inverse function be used? Default is FALSE

Details

This function will get your data ready for processing with many types of ml/ai models.

This is intended to be used inside of the data processor and therefore is an internal function. This documentation exists to explain the process and help the user understand the parameters that can be set in the pre-processor function.

`recipes::step_hyperbolic()`

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://recipes.tidymodels.org/reference/step_hyperbolic.html

Other Data Recipes: hai_data_impute(), hai_data_poly(), hai_data_scale(), hai_data_transform(), pca_your_recipe()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

date_seq <- seq.Date(from = as.Date("2013-01-01"), length.out = 100, by = "month")
val_seq <- rep(rnorm(10, mean = 6, sd = 2), times = 10)
df_tbl <- tibble(
  date_col = date_seq,
  value    = val_seq
)

rec_obj <- recipe(value ~ ., df_tbl)

hai_data_trig(
  .recipe_object = rec_obj,
  value,
  .type_of_scale = "sinh"
)$new_rec_obj |>
  get_juiced_data()
```

---

hai_default_classification_metric_set

Metric Set

Description

Default classification metric sets from yardstick

Usage

```
hai_default_classification_metric_set()
```

Details

Default classification metric sets from yardstick

Value

A yardstick metric set tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Default Metric Sets: `hai_default_regression_metric_set()`

Examples

```
hai_default_classification_metric_set()
```

`hai_default_regression_metric_set` *Metric Set*

Description

Default regression metric sets from `yardstick`

Usage

```
hai_default_regression_metric_set()
```

Details

Default regression metric sets from `yardstick`

Value

A yardstick metric set tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Default Metric Sets: `hai_default_classification_metric_set()`

Examples

```
hai_default_regression_metric_set()
```

`hai_density_hist_plot` *Density Histogram Plot*

Description

this will produce a `ggplot2` or `plotly` histogram plot of the density information provided from the `hai_get_density_data_tbl` function.

Usage

```
hai_density_hist_plot(
  .data,
  .dist_name_col = distribution,
  .value_col = dist_data,
  .alpha = 0.382,
  .interactive = FALSE
)
```

Arguments

`.data`	The data that is produced from using `hai_get_density_data_tbl`
`.dist_name_col`	The column that has the distribution name, should be distribution and that is set as the default.
`.value_col`	The column that contains the x values that comes from the `hai_get_density_data_tbl` function.
`.alpha`	The alpha parameter for ggplot
`.interactive`	This is a Boolean fo TRUE/FALSE and is defaulted to FALSE. TRUE will produce a `plotly` plot.

Details

This will produce a histogram of the density information that is produced from the function `hai_get_density_data_tbl`. It will look for an attribute from the `.data` param to ensure the function was used.

Value

A plot, either `ggplot2` or `plotly`

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Distribution Plots: `hai_density_plot()`, `hai_density_qq_plot()`

Examples

```
library(dplyr)

df <- hai_scale_zero_one_vec(.x = mtcars$mpg) |>
  hai_distribution_comparison_tbl()

dist_data_tbl <- hai_get_dist_data_tbl(df)

hai_density_hist_plot(
  .data = dist_data_tbl,
  .dist_name_col = distribution,
  .value_col = dist_data,
  .alpha = 0.5,
  .interactive = FALSE
)
```

---

hai_density_plot *Density Histogram Plot*

Description

this will produce a ggplot2 or plotly histogram plot of the density information provided from the hai_get_density_data_tbl function.

Usage

```
hai_density_plot(
  .data,
  .dist_name_col,
  .x_col,
  .y_col,
  .size = 1,
  .alpha = 0.382,
  .interactive = FALSE
)
```

Arguments

.data	The data that is produced from using hai_get_density_data_tbl
.dist_name_col	The column that has the distribution name, should be distribution and that is set as the default.
.x_col	The x value from the tidied density object.
.y_col	The y value from the tidied density object.
.size	The size parameter for ggplot.
.alpha	The alpha parameter for ggplot.
.interactive	This is a Boolean fo TRUE/FALSE and is defaulted to FALSE. TRUE will produce a plotly plot.

Details

This will produce a density plot of the density information that is produced from the function `hai_get_density_data_tbl`. It will look for an attribute from the `.data` param to ensure the function was used.

Value

A plot, either `ggplot2` or `plotly`

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Distribution Plots: `hai_density_hist_plot()`, `hai_density_qq_plot()`

Examples

```
library(dplyr)

df <- hai_scale_zero_one_vec(.x = mtcars$mpg) |>
  hai_distribution_comparison_tbl()

tidy_density_tbl <- hai_get_density_data_tbl(df)

hai_density_plot(
  .data = tidy_density_tbl,
  .dist_name_col = distribution,
  .x_col = x,
  .y_col = y,
  .alpha = 0.5,
  .interactive = FALSE
)
```

`hai_density_qq_plot` *Density QQ Plot*

Description

this will produce a `ggplot2` or `plotly` histogram plot of the density information provided from the `hai_get_density_data_tbl` function.

Usage

```
hai_density_qq_plot(
  .data,
  .dist_name_col = distribution,
  .x_col = x,
  .y_col = y,
  .size = 1,
  .alpha = 0.382,
  .interactive = FALSE
)
```

Arguments

.data	The data that is produced from using hai_get_density_data_tbl
.dist_name_col	The column that has the distribution name, should be distribution and that is set as the default.
.x_col	The column that contains the x values that comes from the hai_get_density_data_tbl function.
.y_col	The column that contains the y values that comes from the hai_get_density_data_tbl function.
.size	The size parameter for ggplot
.alpha	The alpha parameter for ggplot
.interactive	This is a Boolean fo TRUE/FALSE and is defaulted to FALSE. TRUE will produce a plotly plot.

Details

This will produce a qq plot of the density information that is produced from the function hai_get_density_data_tbl. It will look for an attribute from the .data param to ensure the function was used.

Value

A plot, either ggplot2 or plotly

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Distribution Plots: hai_density_hist_plot(), hai_density_plot()

Examples

```
library(dplyr)

df <- hai_scale_zero_one_vec(.x = mtcars$mpg) |>
  hai_distribution_comparison_tbl()
```

```
tidy_density_tbl <- hai_get_density_data_tbl(df)

hai_density_qq_plot(
  .data = tidy_density_tbl,
  .dist_name_col = distribution,
  .x_col = x,
  .y_col = y,
  .size = 1,
  .alpha = 0.5,
  .interactive = FALSE
)
```

`hai_distribution_comparison_tbl`

Compare Data Against Distributions

Description

This function will attempt to get some key information on the data you pass to it. It will also automatically normalize the data from 0 to 1. This will not change the distribution just it's scale in order to make sure that many different types of distributions can be fit to the data, which should help identify what the distribution of the passed data could be.

The resulting output has attributes added to it that get used in other functions that are meant to compliment each other.

This function will automatically pass the `.x` parameter to `hai_skewness_vec()` and `hai_kurtosis_vec()` in order to help create the random data from the distributions.

The distributions that can be chosen from are:

Distribution	R stats::dist
normal	rnorm
uniform	runif
exponential	rexp
logistic	rlogis
beta	rbeta
lognormal	rlnorm
gamma	rgamma
weibull	weibull
chisquare	rchisq
cauchy	rcauchy
hypergeometric	rhyper
f	rf
poisson	rpois

Usage

```
hai_distribution_comparison_tbl(
  .x,
  .distributions = c("gamma", "beta"),
  .normalize = TRUE
)
```

Arguments

.x	The numeric vector to analyze.
.distributions	A character vector of distributions to check. For example, c("gamma","beta")
.normalize	A boolean value of TRUE/FALSE, the default is TRUE. This will normalize the data using the hai_scale_zero_one_vec function.

Details

Get information on the empirical distribution of your data along with generated densities of other distributions. This information is in the resulting tibble that is generated. Three columns will generate, Distribution, from the param .distributions, dist_data which is a list vector of density values passed to the underlying stats r distribution function, and density_data, which is the dist_data column passed to list(stats::density(unlist(dist_data)))

This has the effect of giving you the desired vector that can be used in resultant plots (dist_data) or you can interact with the density object itself.

If the skewness of the distribution is negative, then for the gamma and beta distributions the skew is set equal to the kurtosis and the kurtosis is set equal to sqrt((skew)^2)

Value

A tibble.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Distribution Functions: hai_get_density_data_tbl(), hai_get_dist_data_tbl()

Examples

```
x_vec <- hai_scale_zero_one_vec(mtcars$mpg)
df <- hai_distribution_comparison_tbl(
  .x = x_vec,
  .distributions = c("beta", "gamma")
)
df
```

`hai_earth_data_prepper` *Prep Data for Earth - Recipe*

Description

Automatically prep a data.frame/tibble for use in the Earth algorithm.

Usage

```
hai_earth_data_prepper(.data, .recipe_formula)
```

Arguments

`.data`	The data that you are passing to the function. Can be any type of data that is accepted by the `data` parameter of the `recipes::reciep()` function.
`.recipe_formula`	The formula that is going to be passed. For example if you are using the `diamonds` data then the formula would most likely be something like `price ~ .`

Details

This function will automatically prep your data.frame/tibble for use in the Earth algorithm. The Earth algorithm is for classification and regression.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

http://uc-r.github.io/mars

Other Preprocessor: `hai_c50_data_prepper()`, `hai_cubist_data_prepper()`, `hai_glmnet_data_prepper()`, `hai_knn_data_prepper()`, `hai_ranger_data_prepper()`, `hai_svm_poly_data_prepper()`, `hai_svm_rbf_data_prepp`
`hai_xgboost_data_prepper()`

Other Earth: `hai_auto_earth()`

Examples

```
library(ggplot2)
library(tibble)

# Regression
hai_earth_data_prepper(.data = diamonds, .recipe_formula = price ~ .)
reg_obj <- hai_earth_data_prepper(diamonds, price ~ .)
get_juiced_data(reg_obj)

# Classification
Titanic <- as_tibble(Titanic)

hai_earth_data_prepper(Titanic, Survived ~ .)
cla_obj <- hai_earth_data_prepper(Titanic, Survived ~ .)
get_juiced_data(cla_obj)
```

`hai_fourier_augment` *Augment Function Fourier*

Description

Takes a numeric vector(s) or date and will return a tibble of one of the following:

- "sin"
- "cos"
- "sincos"
- c("sin","cos","sincos")

Usage

```
hai_fourier_augment(
  .data,
  .value,
  .period,
  .order,
  .names = "auto",
  .scale_type = c("sin", "cos", "sincos")
)
```

Arguments

`.data`	The data being passed that will be augmented by the function.
`.value`	This is passed `rlang::enquo()` to capture the vectors you want to augment.
`.period`	The number of observations that complete a cycle
`.order`	The fourier term order

.names	The default is "auto"
.scale_type	A character of one of the following: "sin","cos", or sincos" All can be passed by setting the param equal to c("sin","cos","sincos")

Details

Takes a numeric vector or date and will return a vector of one of the following:

- "sin"
- "cos"
- "sincos"
- c("sin","cos","sincos")

This function is intended to be used on its own in order to add columns to a tibble.

Value

A augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: hai_fourier_discrete_augment(), hai_hyperbolic_augment(), hai_polynomial_augment(
hai_scale_zero_one_augment(), hai_scale_zscore_augment(), hai_winsorized_move_augment(),
hai_winsorized_truncate_augment()

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 10
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

hai_fourier_augment(data_tbl, b, .period = 12, .order = 1, .scale_type = "sin")
hai_fourier_augment(data_tbl, b, .period = 12, .order = 1, .scale_type = "cos")
```

`hai_fourier_discrete_augment` *Augment Function Fourier Discrete*

Description

Takes a numeric vector(s) or date and will return a tibble of one of the following:

- "sin"
- "cos"
- "sincos"
- c("sin","cos","sincos") When either of these values falls below zero, then zero else one

Usage

```
hai_fourier_discrete_augment(
  .data,
  .value,
  .period,
  .order,
  .names = "auto",
  .scale_type = c("sin", "cos", "sincos")
)
```

Arguments

`.data`	The data being passed that will be augmented by the function.
`.value`	This is passed `rlang::enquo()` to capture the vectors you want to augment.
`.period`	The number of observations that complete a cycle
`.order`	The fourier term order
`.names`	The default is "auto"
`.scale_type`	A character of one of the following: "sin","cos", or sincos" All can be passed by setting the param equal to c("sin","cos","sincos")

Details

Takes a numeric vector or a date and will return a vector of one of the following:

- "sin"
- "cos"
- "sincos"
- c("sin","cos","sincos")

This function is intended to be used on its own in order to add columns to a tibble.

Value

A augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: hai_fourier_augment(), hai_hyperbolic_augment(), hai_polynomial_augment(), hai_scale_zero_one_augment(), hai_scale_zscore_augment(), hai_winsorized_move_augment(), hai_winsorized_truncate_augment()

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 24
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

hai_fourier_discrete_augment(data_tbl, b, .period = 2 * 12, .order = 1, .scale_type = "sin")
hai_fourier_discrete_augment(data_tbl, b, .period = 2 * 12, .order = 1, .scale_type = "cos")
```

---

hai_fourier_discrete_vec

Vector Function Discrete Fourier

Description

Takes a numeric vector or date and will return a vector of one of the following:

- "sin"
- "cos"
- "sincos" This will do value = sin(x) * cos(x) When either of these values falls below zero, then zero else one

Usage

```
hai_fourier_discrete_vec(
  .x,
  .period,
  .order,
  .scale_type = c("sin", "cos", "sincos")
)
```

Arguments

.x	A numeric vector
.period	The number of observations that complete a cycle
.order	The fourier term order
.scale_type	A character of one of the following: "sin","cos","sincos"

Details

Takes a numeric vector or date and will return a vector of one of the following:

- "sin"
- "cos"
- "sincos"

The internal caluclation is straightforward:

- sin = sin(2 * pi * h * x), where h = .order/.period
- cos = cos(2 * pi * h * x), where h = .order/.period
- sincos = sin(2 * pi * h * x) * cos(2 * pi * h * x) where h = .order/.period

This function can be used on its own. It is also the basis for the function hai_fourier_discrete_augment().

Value

A numeric vector of 1's and 0's

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: hai_fourier_vec(), hai_hyperbolic_vec(), hai_kurtosis_vec(), hai_scale_zero_one_vec(
hai_scale_zscore_vec(), hai_skewness_vec(), hai_winsorized_move_vec(), hai_winsorized_truncate_vec()

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 24
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

vec_1 <- hai_fourier_discrete_vec(data_tbl$a, .period = 12, .order = 1, .scale_type = "sin")
vec_2 <- hai_fourier_discrete_vec(data_tbl$a, .period = 12, .order = 1, .scale_type = "cos")
vec_3 <- hai_fourier_discrete_vec(data_tbl$a, .period = 12, .order = 1, .scale_type = "sincos")

plot(data_tbl$b)
lines(vec_1, col = "blue")
lines(vec_2, col = "red")
lines(vec_3, col = "green")
```

---

hai_fourier_vec *Vector Function Fourier*

Description

Takes a numeric vector and will return a vector of one of the following:

- "sin"
- "cos"
- "sincos" This will do value = sin(x) * cos(x)

Usage

```
hai_fourier_vec(.x, .period, .order, .scale_type = c("sin", "cos", "sincos"))
```

Arguments

.x	A numeric vector
.period	The number of observations that complete a cycle
.order	The fourier term order
.scale_type	A character of one of the following: "sin","cos","sincos"

Details

Takes a numeric vector and will return a vector of one of the following:

- "sin"
- "cos"
- "sincos"

The internal caluclation is straightforward:

- `sin` = `sin(2 * pi * h * x)`, where `h` = `.order/.period`
- `cos` = `cos(2 * pi * h * x)`, where `h` = `.order/.period`
- `sincos` = `sin(2 * pi * h * x) * cos(2 * pi * h * x)` where `h` = `.order/.period`

This function can be used on it's own. It is also the basis for the function `hai_fourier_augment()`.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: `hai_fourier_discrete_vec()`, `hai_hyperbolic_vec()`, `hai_kurtosis_vec()`, `hai_scale_zero_one_vec()`, `hai_scale_zscore_vec()`, `hai_skewness_vec()`, `hai_winsorized_move_vec()`, `hai_winsorized_truncate_vec()`

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 25
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

vec_1 <- hai_fourier_vec(data_tbl$b, .period = 12, .order = 1, .scale_type = "sin")
vec_2 <- hai_fourier_vec(data_tbl$b, .period = 12, .order = 1, .scale_type = "cos")
vec_3 <- hai_fourier_vec(data_tbl$date_col, .period = 12, .order = 1, .scale_type = "sincos")

plot(data_tbl$b)
lines(vec_1, col = "blue")
lines(vec_2, col = "red")
lines(vec_3, col = "green")
```

hai_get_density_data_tbl *Get Density Data Helper*

Description

This function will return a tibble that can either be nested/unnested, and grouped or un-grouped. The `.data` argument must be the output of the `hai_distribution_comparison_tbl()` function.

Usage

```
hai_get_density_data_tbl(.data, .unnest = TRUE, .group_data = TRUE)
```

Arguments

`.data`	The data from the `hai_distribution_comparison_tbl()` function as this function looks for an attribute of `hai_dist_compare_tbl`
`.unnest`	Should the resulting tibble be un-nested, a Boolean value TRUE/FALSE. The default is TRUE
`.group_data`	Should the resulting tibble be grouped, a Boolean value TRUE/FALSE. The default is FALSE

Details

This function expects to take the output of the `hai_distribution_comparison_tbl()` function. It returns a tibble of the `tidy` density data.

Value

A tibble.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Distribution Functions: `hai_distribution_comparison_tbl()`, `hai_get_dist_data_tbl()`

Examples

```
library(dplyr)

df <- hai_scale_zero_one_vec(.x = mtcars$mpg) |>
  hai_distribution_comparison_tbl()
hai_get_density_data_tbl(df)
```

hai_get_dist_data_tbl *Get Distribution Data Helper*

Description

This function will return a tibble that can either be nested/unnested, and grouped or ungrouped. The `.data` argument must be the output of the `hai_distribution_comparison_tbl()` function.

Usage

```
hai_get_dist_data_tbl(.data, .unnest = TRUE, .group_data = FALSE)
```

Arguments

`.data`	The data from the `hai_distribution_comparison_tbl()` function as this function looks for a class of 'hai_dist_data'
`.unnest`	Should the resulting tibble be unnested, a boolean value TRUE/FALSE. The default is TRUE
`.group_data`	Shold the resulting tibble be grouped, a boolean value TRUE/FALSE. The default is FALSE

Details

This function expects to take the output of the `hai_distribution_comparison_tbl()` function. It returns a tibble of the distribution and the randomly generated data produced from the associated stats r function like `rnorm`

Value

A tibble.

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Distribution Functions: `hai_distribution_comparison_tbl()`, `hai_get_density_data_tbl()`

Examples

```
library(dplyr)

df <- hai_scale_zero_one_vec(.x = mtcars$mpg) |>
  hai_distribution_comparison_tbl()
hai_get_dist_data_tbl(df)
```

`hai_glmnet_data_prepper` *Prep Data for glmnet - Recipe*

Description

Automatically prep a data.frame/tibble for use in the glmnet algorithm.

Usage

```
hai_glmnet_data_prepper(.data, .recipe_formula)
```

Arguments

`.data`	The data that you are passing to the function. Can be any type of data that is accepted by the `data` parameter of the `recipes::reciep()` function.
`.recipe_formula`	The formula that is going to be passed. For example if you are using the `iris` data then the formula would most likely be something like `Species ~ .`

Details

This function will automatically prep your data.frame/tibble for use in the glmnet algorithm. It expects data to be presented in a certain fashion.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Preprocessor: `hai_c50_data_prepper()`, `hai_cubist_data_prepper()`, `hai_earth_data_prepper()`, `hai_knn_data_prepper()`, `hai_ranger_data_prepper()`, `hai_svm_poly_data_prepper()`, `hai_svm_rbf_data_prepper()`, `hai_xgboost_data_prepper()`

Other knn: `hai_knn_data_prepper()`

Examples

```
library(ggplot2)
library(tibble)

Titanic <- as_tibble(Titanic)

hai_glmnet_data_prepper(.data = Titanic, .recipe_formula = Survived ~ .)
rec_obj <- hai_glmnet_data_prepper(Titanic, Survived ~ .)
get_juiced_data(rec_obj)
```

---

hai_histogram_facet_plot

Histogram Facet Plot

Description

This function expects a data.frame/tibble and will return a faceted histogram.

Usage

```
hai_histogram_facet_plot(
  .data,
  .bins = 10,
  .scale_data = FALSE,
  .ncol = 5,
  .fct_reorder = FALSE,
  .fct_rev = FALSE,
  .fill = "steelblue",
  .color = "white",
  .scale = "free",
  .interactive = FALSE
)
```

Arguments

.data	The data you want to pass to the function.
.bins	The number of bins for the histograms.
.scale_data	This is a boolean set to FALSE. TRUE will use hai_scale_zero_one_vec() to [0, 1] scale the data.
.ncol	The number of columns for the facet_warp argument.
.fct_reorder	Should the factor column be reordered? TRUE/FALSE, default of FALSE
.fct_rev	Should the factor column be reversed? TRUE/FALSE, default of FALSE
.fill	Default is steelblue
.color	Default is 'white'
.scale	Default is 'free'
.interactive	Default is FALSE, TRUE will produce a plotly plot.

Details

Takes in a data.frame/tibble and returns a faceted historgram.

Value

A ggplot or plotly plot

Author(s)

Steven P. Sanderson II, MPH

Examples

```
hai_histogram_facet_plot(.data = iris)
hai_histogram_facet_plot(.data = iris, .scale_data = TRUE)
```

---

hai_hyperbolic_augment

Augment Function Hyperbolic

Description

Takes a numeric vector(s) or date and will return a tibble of one of the following:

- "sin"
- "cos"
- "tan"
- "sincos"
- c("sin","cos","tan", "sincos")

Usage

```
hai_hyperbolic_augment(
  .data,
  .value,
  .names = "auto",
  .scale_type = c("sin", "cos", "tan", "sincos")
)
```

Arguments

.data	The data being passed that will be augmented by the function.
.value	This is passed `rlang::enquo()` to capture the vectors you want to augment.
.names	The default is "auto"
.scale_type	A character of one of the following: "sin","cos","tan", "sincos" All can be passed by setting the param equal to c("sin","cos","tan","sincos")

Details

Takes a numeric vector or date and will return a vector of one of the following:

- "sin"
- "cos"
- "tan"
- "sincos"
- c("sin","cos","tan", "sincos")

This function is intended to be used on its own in order to add columns to a tibble.

Value

A augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: `hai_fourier_augment()`, `hai_fourier_discrete_augment()`, `hai_polynomial_augment()`, `hai_scale_zero_one_augment()`, `hai_scale_zscore_augment()`, `hai_winsorized_move_augment()`, `hai_winsorized_truncate_augment()`

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 10
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

hai_hyperbolic_augment(data_tbl, b, .scale_type = "sin")
hai_hyperbolic_augment(data_tbl, b, .scale_type = "tan")
```

`hai_hyperbolic_vec` *Vector Function Hyperbolic*

Description

Takes a numeric vector and will return a vector of one of the following:

- "sin"
- "cos"
- "tan"
- "sincos" This will do value = sin(x) * cos(x)

Usage

```
hai_hyperbolic_vec(.x, .scale_type = c("sin", "cos", "tan", "sincos"))
```

Arguments

`.x`	A numeric vector
`.scale_type`	A character of one of the following: "sin","cos","tan","sincos"

Details

Takes a numeric vector and will return a vector of one of the following:

- "sin"
- "cos"
- "tan"
- "sincos"

This function can be used on it's own. It is also the basis for the function `hai_hyperbolic_augment()`.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: `hai_fourier_discrete_vec()`, `hai_fourier_vec()`, `hai_kurtosis_vec()`, `hai_scale_zero_one_vec()`, `hai_scale_zscore_vec()`, `hai_skewness_vec()`, `hai_winsorized_move_vec()`, `hai_winsorized_truncate_vec()`

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 25
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

vec_1 <- hai_hyperbolic_vec(data_tbl$b, .scale_type = "sin")
vec_2 <- hai_hyperbolic_vec(data_tbl$b, .scale_type = "cos")
vec_3 <- hai_hyperbolic_vec(data_tbl$b, .scale_type = "sincos")

plot(data_tbl$b)
lines(vec_1, col = "blue")
lines(vec_2, col = "red")
lines(vec_3, col = "green")
```

---

hai_kmeans_automl *Automatic K-Means H2O*

Description

DEPRECATED: This function is deprecated and will be removed in a future version. The h2o dependency is being removed from healthyR.ai. Please use alternative clustering methods available in the package.

This is a wrapper around the `h2o::h2o.kmeans()` function that will return a list object with a lot of useful and easy to use tidy style information.

Usage

```
hai_kmeans_automl(
  .data,
  .split_ratio = 0.8,
  .seed = 1234,
  .centers = 10,
  .standardize = TRUE,
  .print_model_summary = TRUE,
  .predictors,
  .categorical_encoding = "auto",
  .initialization_mode = "Furthest",
  .max_iterations = 100
)
```

Arguments

`.data`	The data that is to be passed for clustering.
`.split_ratio`	The ratio for training and testing splits.
`.seed`	The default is 1234, but can be set to any integer.
`.centers`	The default is 1. Specify the number of clusters (groups of data) in a data set.
`.standardize`	The default is set to TRUE. When TRUE all numeric columns will be set to zero mean and unit variance.
`.print_model_summary`	This is a boolean and controls if the model summary is printed to the console. The default is TRUE.
`.predictors`	This must be in the form of c("column_1", "column_2", ... "column_n")
`.categorical_encoding`	Can be one of the following: • "auto" • "enum" • "one_hot_explicit" • "binary" • "eigen" • "label_encoder" • "sort_by_response" • "enum_limited"
`.initialization_mode`	This can be one of the following: • "Random" • "Furthest (default) • "PlusPlus"
`.max_iterations`	The default is 100. This specifies the number of training iterations

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Kmeans: `hai_kmeans_automl_predict()`, `hai_kmeans_mapped_tbl()`, `hai_kmeans_obj()`, `hai_kmeans_scree_data_tbl()`, `hai_kmeans_scree_plt()`, `hai_kmeans_tidy_tbl()`, `hai_kmeans_user_item_tbl()`

Examples

```
## Not run:
h2o.init()
output <- hai_kmeans_automl(
  .data = iris,
  .predictors = c("Sepal.Width", "Sepal.Length", "Petal.Width", "Petal.Length"),
  .standardize = FALSE
)
h2o.shutdown()

## End(Not run)
```

---

hai_kmeans_automl_predict

Automatic K-Means H2O

Description

DEPRECATED: This function is deprecated and will be removed in a future version. The h2o dependency is being removed from healthyR.ai. Please use alternative clustering methods available in the package.

This is a wrapper around the `h2o::h2o.predict()` function that will return a list object with a lot of useful and easy to use tidy style information.

Usage

```
hai_kmeans_automl_predict(.input)
```

Arguments

`.input`	This is the output of the `hai_kmeans_automl()` function.

Details

This function will internally take in the output assigned from the `hai_kmeans_automl()` function only and return a list of useful information. The items that are returned are as follows:

1. prediction - The h2o dataframe of predictions
2. prediction_tbl - The h2o predictions in tibble format
3. valid_tbl - The validation data in tibble format
4. pred_full_tbl - The entire validation set with the predictions attached using `base::cbind()`. The predictions are in a column called `predicted_cluster` and are in the formate of a factor using `forcats::as_factor()`

Value

A list object

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Kmeans: hai_kmeans_automl(), hai_kmeans_mapped_tbl(), hai_kmeans_obj(), hai_kmeans_scree_data_tbl(
hai_kmeans_scree_plt(), hai_kmeans_tidy_tbl(), hai_kmeans_user_item_tbl()

Examples

```
## Not run:
h2o.init()

output <- hai_kmeans_automl(
  .data = iris,
  .predictors = c("Sepal.Width", "Sepal.Length", "Petal.Width", "Petal.Length"),
  .standardize = FALSE
)

pred <- hai_kmeans_automl_predict(output)

h2o.shutdown()

## End(Not run)
```

---

hai_kmeans_mapped_tbl *K-Means Mapping Function*

Description

Create a tibble that maps the hai_kmeans_obj() using purrr::map() to create a nested data.frame/tibble that holds n centers. This tibble will be used to help create a scree plot.

Usage

```
hai_kmeans_mapped_tbl(.data, .centers = 15)

kmeans_mapped_tbl(.data, .centers = 15)
```

Arguments

.data	You must have a tibble in the working environment from the hai_kmeans_user_item_tbl()
.centers	How many different centers do you want to try

Details

Takes in a single parameter of .centers. This is used to create the tibble and map the hai_kmeans_obj() function down the list creating a nested tibble.

Value

A nested tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Scree_plot

Other Kmeans: hai_kmeans_automl(), hai_kmeans_automl_predict(), hai_kmeans_obj(), hai_kmeans_scree_data_tbl(), hai_kmeans_scree_plt(), hai_kmeans_tidy_tbl(), hai_kmeans_user_item_tbl()

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()

ui_tbl <- hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
  .col_input = payer_grouping,
  .record_input = record
)

hai_kmeans_mapped_tbl(ui_tbl)
```

---

hai_kmeans_obj *K-Means Object*

Description

Takes the output of the hai_kmeans_user_item_tbl() function and applies the k-means algorithm to it using stats::kmeans()

Usage

```
hai_kmeans_obj(.data, .centers = 5)

kmeans_obj(.data, .centers = 5)
```

Arguments

.data	The data that gets passed from hai_kmeans_user_item_tbl()
.centers	How many initial centers to start with

Details

Uses the stats::kmeans() function and creates a wrapper around it.

Value

A stats k-means object

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Kmeans: hai_kmeans_automl(), hai_kmeans_automl_predict(), hai_kmeans_mapped_tbl(), hai_kmeans_scree_data_tbl(), hai_kmeans_scree_plt(), hai_kmeans_tidy_tbl(), hai_kmeans_user_item_tbl()

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()

hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
  .col_input = payer_grouping,
  .record_input = record
) |>
  hai_kmeans_obj()
```

`hai_kmeans_scree_data_tbl` *K-Means Scree Plot Data Table*

Description

Take data from the `hai_kmeans_mapped_tbl()` and unnest it into a tibble for inspection and for use in the `hai_kmeans_scree_plt()` function.

Usage

```
hai_kmeans_scree_data_tbl(.data)

kmeans_scree_data_tbl(.data)
```

Arguments

`.data`	You must have a tibble in the working environment from the `hai_kmeans_mapped_tbl()`

Details

Takes in a single parameter of .data from `hai_kmeans_mapped_tbl()` and transforms it into a tibble that is used for `hai_kmeans_scree_plt()`. It will show the values (tot.withinss) at each center.

Value

A nested tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Kmeans: `hai_kmeans_automl()`, `hai_kmeans_automl_predict()`, `hai_kmeans_mapped_tbl()`, `hai_kmeans_obj()`, `hai_kmeans_scree_plt()`, `hai_kmeans_tidy_tbl()`, `hai_kmeans_user_item_tbl()`

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()
```

```
ui_tbl <- hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
  .col_input = payer_grouping,
  .record_input = record
)

kmm_tbl <- hai_kmeans_mapped_tbl(ui_tbl)

hai_kmeans_scree_data_tbl(kmm_tbl)
```

`hai_kmeans_scree_plt` *K-Means Scree Plot*

Description

Create a scree-plot from the `hai_kmeans_mapped_tbl()` function.

Usage

```
hai_kmeans_scree_plt(.data)

kmeans_scree_plt(.data)

hai_kmeans_scree_plot(.data)
```

Arguments

`.data`	The data from the `hai_kmeans_mapped_tbl()` function

Details

Outputs a scree-plot

Value

A ggplot2 plot

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Scree_plot

Other Kmeans: `hai_kmeans_automl()`, `hai_kmeans_automl_predict()`, `hai_kmeans_mapped_tbl()`, `hai_kmeans_obj()`, `hai_kmeans_scree_data_tbl()`, `hai_kmeans_tidy_tbl()`, `hai_kmeans_user_item_tbl()`

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()

ui_tbl <- hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
  .col_input = payer_grouping,
  .record_input = record
)

kmm_tbl <- hai_kmeans_mapped_tbl(ui_tbl)

hai_kmeans_scree_plt(.data = kmm_tbl)
```

---

hai_kmeans_tidy_tbl *K-Means Object Tidy Functions*

Description

K-Means tidy functions

Usage

```
hai_kmeans_tidy_tbl(.kmeans_obj, .data, .tidy_type = "tidy")

kmeans_tidy_tbl(.kmeans_obj, .data, .tidy_type = "tidy")
```

Arguments

.kmeans_obj	A stats::kmeans() object
.data	The user item tibble created from hai_kmeans_user_item_tbl()
.tidy_type	"tidy","glance", or "augment"

Details

Takes in a k-means object and its associated user item tibble and then returns one of the items asked for. Either: broom::tidy(), broom::glance() or broom::augment(). The function defaults to broom::tidy().

Value

A tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Kmeans: hai_kmeans_automl(), hai_kmeans_automl_predict(), hai_kmeans_mapped_tbl(), hai_kmeans_obj(), hai_kmeans_scree_data_tbl(), hai_kmeans_scree_plt(), hai_kmeans_user_item_tbl()

Examples

```
library(healthyR.data)
library(dplyr)
library(broom)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()

uit_tbl <- hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
  .col_input = payer_grouping,
  .record_input = record
)

km_obj <- hai_kmeans_obj(uit_tbl)

hai_kmeans_tidy_tbl(
  .kmeans_obj = km_obj,
  .data = uit_tbl,
  .tidy_type = "augment"
)

hai_kmeans_tidy_tbl(
  .kmeans_obj = km_obj,
  .data = uit_tbl,
  .tidy_type = "glance"
)

hai_kmeans_tidy_tbl(
  .kmeans_obj = km_obj,
  .data = uit_tbl,
  .tidy_type = "tidy"
) |>
```

```
glimpse()
```

`hai_kmeans_user_item_tbl` *K-Means User Item Tibble*

Description

Takes in a data.frame/tibble and transforms it into an aggregated/normalized user-item tibble of proportions. The user will need to input the parameters for the rows/user and the columns/items.

Usage

```
hai_kmeans_user_item_tbl(.data, .row_input, .col_input, .record_input)

kmeans_user_item_tbl(.data, .row_input, .col_input, .record_input)
```

Arguments

`.data`	The data that you want to transform
`.row_input`	The column that is going to be the row (user)
`.col_input`	The column that is going to be the column (item)
`.record_input`	The column that is going to be summed up for the aggregation and normalization process.

Details

This function should be used before using a k-mean model. This is commonly referred to as a user-item matrix because "users" tend to be on the rows and "items" (e.g. orders) on the columns. You must supply a column that can be summed for the aggregation and normalization process to occur.

Value

A aggregated/normalized user item tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Kmeans: `hai_kmeans_automl()`, `hai_kmeans_automl_predict()`, `hai_kmeans_mapped_tbl()`, `hai_kmeans_obj()`, `hai_kmeans_scree_data_tbl()`, `hai_kmeans_scree_plt()`, `hai_kmeans_tidy_tbl()`

Examples

```
library(healthyR.data)
library(dplyr)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()

hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
  .col_input = payer_grouping,
  .record_input = record
)
```

---

hai_knn_data_prepper *Prep Data for k-NN - Recipe*

Description

Automatically prep a data.frame/tibble for use in the k-NN algorithm.

Usage

```
hai_knn_data_prepper(.data, .recipe_formula)
```

Arguments

`.data`	The data that you are passing to the function. Can be any type of data that is accepted by the `data` parameter of the `recipes::reciep()` function.
`.recipe_formula`	The formula that is going to be passed. For example if you are using the `iris` data then the formula would most likely be something like `Species ~ .`

Details

This function will automatically prep your data.frame/tibble for use in the k-NN algorithm. The k-NN algorithm is a lazy learning classification algorithm. It expects data to be presented in a certain fashion.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Preprocessor: hai_c50_data_prepper(), hai_cubist_data_prepper(), hai_earth_data_prepper(), hai_glmnet_data_prepper(), hai_ranger_data_prepper(), hai_svm_poly_data_prepper(), hai_svm_rbf_data_prepper(), hai_xgboost_data_prepper()

Other knn: hai_glmnet_data_prepper()

Examples

```
library(ggplot2)
library(tibble)

Titanic <- as_tibble(Titanic)

hai_knn_data_prepper(.data = Titanic, .recipe_formula = Survived ~ .)
rec_obj <- hai_knn_data_prepper(iris, Species ~ .)
get_juiced_data(rec_obj)
```

---

hai_kurtosis_vec *Compute Kurtosis of a Vector*

Description

This function takes in a vector as it's input and will return the kurtosis of that vector. The length of this vector must be at least four numbers. The kurtosis explains the sharpness of the peak of a distribution of data.
`((1/n) * sum(x - mu})^4) / (((()1/n) * sum(x - mu)^2)^2`

Usage

```
hai_kurtosis_vec(.x)
```

Arguments

.x	A numeric vector of length four or more.

Details

A function to return the kurtosis of a vector.

Value

The kurtosis of a vector

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Kurtosis

Other Vector Function: hai_fourier_discrete_vec(), hai_fourier_vec(), hai_hyperbolic_vec(), hai_scale_zero_one_vec(), hai_scale_zscore_vec(), hai_skewness_vec(), hai_winsorized_move_vec(), hai_winsorized_truncate_vec()

Examples

```
hai_kurtosis_vec(rnorm(100, 3, 2))
```

---

hai_polynomial_augment

Augment Polynomial Features

Description

This function takes in a data table and a predictor column. A user can either create their own formula using the .formula parameter or, if they leave the default of NULL then the user must enter a .degree **AND** .pred_col column.

Usage

```
hai_polynomial_augment(
  .data,
  .formula = NULL,
  .pred_col = NULL,
  .degree = 1,
  .new_col_prefix = "nt_"
)
```

Arguments

.data	The data being passed that will be augmented by the function.
.formula	This should be a valid formula like 'y ~ .^2' or NULL.
.pred_col	This is passed rlang::enquo() to capture the vector that you designate as the 'y' column.
.degree	This should be an integer and is used to set the degree in the poly function. The degree must be less than the unique data points or it will error out.
.new_col_prefix	The default is "nt_" which stands for "new_term". You can set this to whatever you like, as long as it is a quoted string.

Details

A valid data.frame/tibble must be passed to this function. It is required that a user either enter a `.formula` or a `.degree` **AND** `.pred_col` otherwise this function will stop and error out.

Under the hood this function will create a `stats::poly()` function if the `.formula` is left as `NULL`. For example:

- .formula = A ~ .^2
- OR .degree = 2, .pred_col = A

There is also a parameter `.new_col_prefix` which will add a character string to the column names so that they are easily identified further down the line. The default is 'nt_'

Value

An augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: `hai_fourier_augment()`, `hai_fourier_discrete_augment()`, `hai_hyperbolic_augment()`, `hai_scale_zero_one_augment()`, `hai_scale_zscore_augment()`, `hai_winsorized_move_augment()`, `hai_winsorized_truncate_augment()`

Examples

```
suppressPackageStartupMessages(library(dplyr))
data_tbl <- data.frame(
  A = c(0, 2, 4),
  B = c(1, 3, 5),
  C = c(2, 4, 6)
)

hai_polynomial_augment(.data = data_tbl, .pred_col = A, .degree = 2, .new_col_prefix = "n")
hai_polynomial_augment(.data = data_tbl, .formula = A ~ .^2, .degree = 1)
```

---

hai_ranger_data_prepper

Prep Data for Ranger - Recipe

Description

Automatically prep a data.frame/tibble for use in the Ranger algorithm.

Usage

```
hai_ranger_data_prepper(.data, .recipe_formula)
```

Arguments

.data	The data that you are passing to the function. Can be any type of data that is accepted by the data parameter of the recipes::reciep() function.
.recipe_formula	The formula that is going to be passed. For example if you are using the diamonds data then the formula would most likely be something like price ~ .

Details

This function will automatically prep your data.frame/tibble for use in the Ranger algorithm.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/rand_forest.html

Other Preprocessor: hai_c50_data_prepper(), hai_cubist_data_prepper(), hai_earth_data_prepper(), hai_glmnet_data_prepper(), hai_knn_data_prepper(), hai_svm_poly_data_prepper(), hai_svm_rbf_data_prepper(), hai_xgboost_data_prepper()

Other Ranger: hai_auto_ranger()

Examples

```
library(ggplot2)
library(tibble)

# Regression
hai_ranger_data_prepper(.data = diamonds, .recipe_formula = price ~ .)
reg_obj <- hai_ranger_data_prepper(diamonds, price ~ .)
get_juiced_data(reg_obj)

# Classification
Titanic <- as_tibble(Titanic)

hai_ranger_data_prepper(Titanic, Survived ~ .)
cla_obj <- hai_ranger_data_prepper(Titanic, Survived ~ .)
get_juiced_data(cla_obj)
```

hai_range_statistic *Get the range statistic*

Description

Takes in a numeric vector and returns back the range of that vector

Usage

```
hai_range_statistic(.x)
```

Arguments

.x	A numeric vector

Details

Takes in a numeric vector and returns the range of that vector using the `diff` and `range` functions.

Value

A single number, the range statistic

Author(s)

Steven P. Sandeson II, MPH

Examples

```
hai_range_statistic(seq(1:10))
```

hai_scale_color_colorblind *Provide Colorblind Compliant Colors*

Description

8 Hex RGB color definitions suitable for charts for colorblind people.

Usage

```
hai_scale_color_colorblind(..., theme = "hai")
```

Arguments

...	Data passed in from a ggplot object
theme	Right now this is hai only. Anything else will render an error.

Details

This function is used in others in order to help render plots for those that are color blind.

Value

A gggplot layer

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Color_Blind: color_blind(), hai_scale_fill_colorblind()

---

hai_scale_fill_colorblind

Provide Colorblind Compliant Colors

Description

8 Hex RGB color definitions suitable for charts for colorblind people.

Usage

```
hai_scale_fill_colorblind(..., theme = "hai")
```

Arguments

...	Data passed in from a ggplot object
theme	Right now this is hai only. Anything else will render an error.

Details

This function is used in others in order to help render plots for those that are color blind.

Value

A gggplot layer

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Color_Blind: color_blind(), hai_scale_color_colorblind()

`hai_scale_zero_one_augment` *Augment Function Scale Zero One*

Description

Takes a numeric vector and will return a vector that has been scaled from [0,1]

Usage

```
hai_scale_zero_one_augment(.data, .value, .names = "auto")
```

Arguments

.data	The data being passed that will be augmented by the function.
.value	This is passed rlang::enquo() to capture the vectors you want to augment.
.names	This is set to 'auto' by default but can be a user supplied character string.

Details

Takes a numeric vector and will return a vector that has been scaled from [0,1] The input vector must be numeric. The computation is fairly straightforward. This may be helpful when trying to compare the distributions of data where a distribution like beta from the fitdistrplus package which requires data to be between 0 and 1

$$y[h] = (x - min(x))/(max(x) - min(x))$$

This function is intended to be used on its own in order to add columns to a tibble.

Value

An augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: hai_fourier_augment(), hai_fourier_discrete_augment(), hai_hyperbolic_augment(), hai_polynomial_augment(), hai_scale_zscore_augment(), hai_winsorized_move_augment(), hai_winsorized_truncate_augment()

Other Scale: hai_scale_zero_one_vec(), hai_scale_zscore_augment(), hai_scale_zscore_vec(), step_hai_scale_zscore()

Examples

```
df <- data.frame(x = rnorm(100, 2, 1))
hai_scale_zero_one_augment(df, x)
```

`hai_scale_zero_one_vec`

Vector Function Scale to Zero and One

Description

Takes a numeric vector and will return a vector that has been scaled from `[0,1]`

Usage

```
hai_scale_zero_one_vec(.x)
```

Arguments

`.x`	A numeric vector to be scaled from `[0,1]` inclusive.

Details

Takes a numeric vector and will return a vector that has been scaled from `[0,1]` The input vector must be numeric. The computation is fairly straightforward. This may be helpful when trying to compare the distributions of data where a distribution like beta from the `fitdistrplus` package which requires data to be between 0 and 1

$$y[h] = (x - min(x))/(max(x) - min(x))$$

This function can be used on it's own. It is also the basis for the function `hai_scale_zero_one_augment()`.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: `hai_fourier_discrete_vec()`, `hai_fourier_vec()`, `hai_hyperbolic_vec()`, `hai_kurtosis_vec()`, `hai_scale_zscore_vec()`, `hai_skewness_vec()`, `hai_winsorized_move_vec()`, `hai_winsorized_truncate_vec()`

Other Scale: `hai_scale_zero_one_augment()`, `hai_scale_zscore_augment()`, `hai_scale_zscore_vec()`, `step_hai_scale_zscore()`

Examples

```
vec_1 <- rnorm(100, 2, 1)
vec_2 <- hai_scale_zero_one_vec(vec_1)

dens_1 <- density(vec_1)
dens_2 <- density(vec_2)
max_x <- max(dens_1$x, dens_2$x)
max_y <- max(dens_1$y, dens_2$y)
plot(dens_1,
  asp = max_y / max_x, main = "Density vec_1 (Red) and vec_2 (Blue)",
  col = "red", xlab = "", ylab = "Density of Vec 1 and Vec 2"
)
lines(dens_2, col = "blue")
```

---

hai_scale_zscore_augment

Augment Function Scale Zero One

Description

Takes a numeric vector and will return a vector that has been scaled by mean and standard deviation

Usage

```
hai_scale_zscore_augment(.data, .value, .names = "auto")
```

Arguments

.data	The data being passed that will be augmented by the function.
.value	This is passed rlang::enquo() to capture the vectors you want to augment.
.names	This is set to 'auto' by default but can be a user supplied character string.

Details

Takes a numeric vector and will return a vector that has been scaled by mean and standard deviation.

The input vector must be numeric. The computation is fairly straightforward. This may be helpful when trying to compare the distributions of data where a distribution like beta from the fitdistrplus package which requires data to be between 0 and 1

$$y[h] = (x - mean(x)/sd(x))$$

This function is intended to be used on its own in order to add columns to a tibble.

Value

An augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Augment Function: hai_fourier_augment(), hai_fourier_discrete_augment(), hai_hyperbolic_augment(), hai_polynomial_augment(), hai_scale_zero_one_augment(), hai_winsorized_move_augment(), hai_winsorized_truncate_augment()

Other Scale: hai_scale_zero_one_augment(), hai_scale_zero_one_vec(), hai_scale_zscore_vec(), step_hai_scale_zscore()

Examples

```
df <- data.frame(x = mtcars$mpg)
hai_scale_zscore_augment(df, x)
```

---

hai_scale_zscore_vec *Vector Function Scale to Zero and One*

Description

Takes a numeric vector and will return a vector that has been scaled from by mean and standard deviation

Usage

```
hai_scale_zscore_vec(.x)
```

Arguments

.x	A numeric vector to be scaled by mean and standard deviation inclusive.

Details

Takes a numeric vector and will return a vector that has been scaled from mean and standard deviation.

The input vector must be numeric. The computation is fairly straightforward. This may be helpful when trying to compare the distributions of data where a distribution like beta from the fitdistrplus package which requires data to be between 0 and 1

$$y[h] = (x - mean(x)/sd(x))$$

This function can be used on it's own. It is also the basis for the function hai_scale_zscore_augment().

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

Other Vector Function: hai_fourier_discrete_vec(), hai_fourier_vec(), hai_hyperbolic_vec(), hai_kurtosis_vec(), hai_scale_zero_one_vec(), hai_skewness_vec(), hai_winsorized_move_vec(), hai_winsorized_truncate_vec()

Other Scale: hai_scale_zero_one_augment(), hai_scale_zero_one_vec(), hai_scale_zscore_augment(), step_hai_scale_zscore()

Examples

```
vec_1 <- mtcars$mpg
vec_2 <- hai_scale_zscore_vec(vec_1)

ax <- pretty(min(vec_1, vec_2):max(vec_1, vec_2), n = 12)

hist(vec_1, breaks = ax, col = "blue")
hist(vec_2, breaks = ax, col = "red", add = TRUE)
```

---

hai_skewed_features *Get Skewed Feature Columns*

Description

Takes in a data.frame/tibble and returns a vector of names of the columns that are skewed.

Usage

```
hai_skewed_features(.data, .threshold = 0.6, .drop_keys = NULL)
```

Arguments

.data	The data.frame/tibble you are passing in.
.threshold	A level of skewness that indicates where you feel a column should be considered skewed.
.drop_keys	A c() character vector of columns you do not want passed to the function.

Details

Takes in a data.frame/tibble and returns a vector of names of the skewed columns. There are two other parameters. The first is the .threshold parameter that is set to the level of skewness you want in order to consider the column too skewed. The second is .drop_keys, these are columns you don't want to be considered for whatever reason in the skewness calculation.

Value

A character vector of column names that are skewed.

Author(s)

Steven P. Sandeson II, MPH

Examples

```
hai_skewed_features(mtcars)
hai_skewed_features(mtcars, .drop_keys = c("mpg", "hp"))
hai_skewed_features(mtcars, .drop_keys = "hp")
```

---

hai_skewness_vec *Compute Skewness of a Vector*

Description

This function takes in a vector as it's input and will return the skewness of that vector. The length of this vector must be at least four numbers. The skewness explains the 'tailedness' of the distribution of data.
`((1/n) * sum(x - mu})^3) / (((()1/n) * sum(x - mu)^2)^(3/2)`

Usage

```
hai_skewness_vec(.x)
```

Arguments

`.x`	A numeric vector of length four or more.

Details

A function to return the skewness of a vector.

Value

The skewness of a vector

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Skewness

Other Vector Function: hai_fourier_discrete_vec(), hai_fourier_vec(), hai_hyperbolic_vec(), hai_kurtosis_vec(), hai_scale_zero_one_vec(), hai_scale_zscore_vec(), hai_winsorized_move_vec(), hai_winsorized_truncate_vec()

Examples

```
hai_skewness_vec(rnorm(100, 3, 2))
```

---

hai_svm_poly_data_prepper

Prep Data for SVM_Poly - Recipe

Description

Automatically prep a data.frame/tibble for use in the SVM_Poly algorithm.

Usage

```
hai_svm_poly_data_prepper(.data, .recipe_formula)
```

Arguments

.data	The data that you are passing to the function. Can be any type of data that is accepted by the data parameter of the recipes::reciep() function.
.recipe_formula	The formula that is going to be passed. For example if you are using the diamonds data then the formula would most likely be something like price ~ .

Details

This function will automatically prep your data.frame/tibble for use in the SVM_Poly algorithm. The SVM_Poly algorithm is for regression only.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/svm_poly.html

Other Preprocessor: hai_c50_data_prepper(), hai_cubist_data_prepper(), hai_earth_data_prepper(), hai_glmnet_data_prepper(), hai_knn_data_prepper(), hai_ranger_data_prepper(), hai_svm_rbf_data_prepper(hai_xgboost_data_prepper()

Other SVM_Poly: hai_auto_svm_poly()

Examples

```
library(ggplot2)
library(tibble)

# Regression
hai_svm_poly_data_prepper(.data = diamonds, .recipe_formula = price ~ .)
reg_obj <- hai_svm_poly_data_prepper(diamonds, price ~ .)
get_juiced_data(reg_obj)

# Classification
Titanic <- as_tibble(Titanic)

hai_svm_poly_data_prepper(Titanic, Survived ~ .)
cla_obj <- hai_svm_poly_data_prepper(Titanic, Survived ~ .)
get_juiced_data(cla_obj)
```

---

hai_svm_rbf_data_prepper

Prep Data for SVM_RBF - Recipe

Description

Automatically prep a data.frame/tibble for use in the SVM_RBF algorithm.

Usage

```
hai_svm_rbf_data_prepper(.data, .recipe_formula)
```

Arguments

.data	The data that you are passing to the function. Can be any type of data that is accepted by the data parameter of the recipes::reciep() function.
.recipe_formula	The formula that is going to be passed. For example if you are using the diamonds data then the formula would most likely be something like price ~ .

Details

This function will automatically prep your data.frame/tibble for use in the SVM_RBF algorithm. The SVM_RBF algorithm is for regression only.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/svm_rbf.html

Other Preprocessor: hai_c50_data_prepper(), hai_cubist_data_prepper(), hai_earth_data_prepper(), hai_glmnet_data_prepper(), hai_knn_data_prepper(), hai_ranger_data_prepper(), hai_svm_poly_data_prepper hai_xgboost_data_prepper()

Other SVM_RBF: hai_auto_svm_rbf()

Examples

```
library(ggplot2)
library(tibble)

# Regression
hai_svm_rbf_data_prepper(.data = diamonds, .recipe_formula = price ~ .)
reg_obj <- hai_svm_rbf_data_prepper(diamonds, price ~ .)
get_juiced_data(reg_obj)

# Classification
Titanic <- as_tibble(Titanic)

hai_svm_rbf_data_prepper(Titanic, Survived ~ .)
cla_obj <- hai_svm_rbf_data_prepper(Titanic, Survived ~ .)
get_juiced_data(cla_obj)
```

---

hai_umap_list *UMAP Projection*

Description

Create a umap object from the uwot::umap() function.

Usage

```
hai_umap_list(.data, .kmeans_map_tbl, .k_cluster = 5)

umap_list(.data, .kmeans_map_tbl, .k_cluster = 5)
```

Arguments

.data	The data from the hai_kmeans_user_item_tbl() function.
.kmeans_map_tbl	The data from the hai_kmeans_mapped_tbl().
.k_cluster	Pick the desired amount of clusters from your analysis of the scree plot.

Details

This takes in the user item table/matix that is produced by hai_kmeans_user_item_tbl() function. This function uses the defaults of uwot::umap().

Value

A list of tibbles and the umap object

Author(s)

Steven P. Sanderson II, MPH

See Also

- https://cran.r-project.org/package=uwot (CRAN)
- https://github.com/jlmelville/uwot (GitHub)
- https://github.com/jlmelville/uwot (arXiv paper)

Other UMAP: hai_umap_plot()

Examples

```
library(healthyR.data)
library(dplyr)
library(broom)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()

uit_tbl <- hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
```

```
  .col_input = payer_grouping,
  .record_input = record
)

kmm_tbl <- hai_kmeans_mapped_tbl(uit_tbl)

umap_list(.data = uit_tbl, kmm_tbl, 3)
```

`hai_umap_plot` *UMAP and K-Means Cluster Visualization*

Description

Create a UMAP Projection plot.

Usage

```
hai_umap_plot(.data, .point_size = 2, .label = TRUE)

umap_plt(.data, .point_size = 2, .label = TRUE)
```

Arguments

`.data`	The data from the `umap_list()` function.
`.point_size`	The desired size for the points of the plot.
`.label`	Should `ggrepel::geom_label_repel()` be used to display cluster user labels.

Details

This takes in `umap_kmeans_cluster_results_tbl` from the `umap_list()` function output.

Value

A ggplot2 UMAP Projection with clusters represented by colors.

Author(s)

Steven P. Sanderson II, MPH

See Also

- https://cran.r-project.org/package=uwot (CRAN)
- https://github.com/jlmelville/uwot (GitHub)
- https://github.com/jlmelville/uwot (arXiv paper)

Other UMAP: `hai_umap_list()`

Examples

```
library(healthyR.data)
library(dplyr)
library(broom)
library(ggplot2)

data_tbl <- healthyR_data |>
  filter(ip_op_flag == "I") |>
  filter(payer_grouping != "Medicare B") |>
  filter(payer_grouping != "?") |>
  select(service_line, payer_grouping) |>
  mutate(record = 1) |>
  as_tibble()

uit_tbl <- hai_kmeans_user_item_tbl(
  .data = data_tbl,
  .row_input = service_line,
  .col_input = payer_grouping,
  .record_input = record
)

kmm_tbl <- hai_kmeans_mapped_tbl(uit_tbl)

ump_lst <- hai_umap_list(.data = uit_tbl, kmm_tbl, 3)

hai_umap_plot(.data = ump_lst, .point_size = 3)
```

`hai_winsorized_move_augment`

Augment Function Winsorize Move

Description

Takes a numeric vector and will return a tibble with the winsorized values.

Usage

```
hai_winsorized_move_augment(.data, .value, .multiple, .names = "auto")
```

Arguments

`.data`	The data being passed that will be augmented by the function.
`.value`	This is passed `rlang::enquo()` to capture the vectors you want to augment.
`.multiple`	A positive number indicating how many times the the zero center mean absolute deviation should be multiplied by for the scaling parameter.
`.names`	The default is "auto"

Details

Takes a numeric vector and will return a winsorized vector of values that have been moved some multiple from the mean absolute deviation zero center of some vector. The intent of winsorization is to limit the effect of extreme values.

Value

An augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Winsorizing

Other Augment Function: hai_fourier_augment(), hai_fourier_discrete_augment(), hai_hyperbolic_augment(), hai_polynomial_augment(), hai_scale_zero_one_augment(), hai_scale_zscore_augment(), hai_winsorized_truncate_augment()

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 24
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

hai_winsorized_move_augment(data_tbl, a, .multiple = 3)
```

---

hai_winsorized_move_vec

Vector Function Winsorize Move

Description

Takes a numeric vector and will return a vector of winsorized values.

Usage

```
hai_winsorized_move_vec(.x, .multiple = 3)
```

Arguments

.x	A numeric vector
.multiple	A positive number indicating how many times the the zero center mean absolute deviation should be multiplied by for the scaling parameter.

Details

Takes a numeric vector and will return a winsorized vector of values that have been moved some multiple from the mean absolute deviation zero center of some vector. The intent of winsorization is to limit the effect of extreme values.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Winsorizing

This function can be used on it's own. It is also the basis for the function hai_winsorized_move_augment().

Other Vector Function: hai_fourier_discrete_vec(), hai_fourier_vec(), hai_hyperbolic_vec(), hai_kurtosis_vec(), hai_scale_zero_one_vec(), hai_scale_zscore_vec(), hai_skewness_vec(), hai_winsorized_truncate_vec()

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 25
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

vec_1 <- hai_winsorized_move_vec(data_tbl$a, .multiple = 1)

plot(data_tbl$a)
lines(data_tbl$a)
lines(vec_1, col = "blue")
```

`hai_winsorized_truncate_augment` *Augment Function Winsorize Truncate*

Description

Takes a numeric vector and will return a tibble with the winsorized values.

Usage

```
hai_winsorized_truncate_augment(.data, .value, .fraction, .names = "auto")
```

Arguments

`.data`	The data being passed that will be augmented by the function.
`.value`	This is passed `rlang::enquo()` to capture the vectors you want to augment.
`.fraction`	A positive fractional between 0 and 0.5 that is passed to the `stats::quantile` paramater of `probs`.
`.names`	The default is "auto"

Details

Takes a numeric vector and will return a winsorized vector of values that have been truncated if they are less than or greater than some defined fraction of a quantile. The intent of winsorization is to limit the effect of extreme values.

Value

An augmented tibble

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Winsorizing

Other Augment Function: `hai_fourier_augment()`, `hai_fourier_discrete_augment()`, `hai_hyperbolic_augment()`, `hai_polynomial_augment()`, `hai_scale_zero_one_augment()`, `hai_scale_zscore_augment()`, `hai_winsorized_move_augment()`

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 24
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

hai_winsorized_truncate_augment(data_tbl, a, .fraction = 0.05)
```

`hai_winsorized_truncate_vec` *Vector Function Winsorize Truncate*

Description

Takes a numeric vector and will return a vector of winsorized values.

Usage

```
hai_winsorized_truncate_vec(.x, .fraction = 0.05)
```

Arguments

`.x`	A numeric vector
`.fraction`	A positive fractional between 0 and 0.5 that is passed to the `stats::quantile` paramater of `probs`.

Details

Takes a numeric vector and will return a winsorized vector of values that have been truncated if they are less than or greater than some defined fraction of a quantile. The intent of winsorization is to limit the effect of extreme values.

Value

A numeric vector

Author(s)

Steven P. Sanderson II, MPH

See Also

https://en.wikipedia.org/wiki/Winsorizing

This function can be used on it's own. It is also the basis for the function hai_winsorized_truncate_augment().

Other Vector Function: hai_fourier_discrete_vec(), hai_fourier_vec(), hai_hyperbolic_vec(), hai_kurtosis_vec(), hai_scale_zero_one_vec(), hai_scale_zscore_vec(), hai_skewness_vec(), hai_winsorized_move_vec()

Examples

```
suppressPackageStartupMessages(library(dplyr))

len_out <- 25
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

vec_1 <- hai_winsorized_truncate_vec(data_tbl$a, .fraction = 0.05)

plot(data_tbl$a)
lines(data_tbl$a)
lines(vec_1, col = "blue")
```

---

hai_xgboost_data_prepper

Prep Data for XGBoost - Recipe

Description

Automatically prep a data.frame/tibble for use in the xgboost algorithm.

Usage

```
hai_xgboost_data_prepper(.data, .recipe_formula)
```

Arguments

.data	The data that you are passing to the function. Can be any type of data that is accepted by the data parameter of the recipes::reciep() function.
.recipe_formula	The formula that is going to be passed. For example if you are using the diamonds data then the formula would most likely be something like price ~ .

Details

This function will automatically prep your data.frame/tibble for use in the XGBoost algorithm.

This function will output a recipe specification.

Value

A recipe object

Author(s)

Steven P. Sanderson II, MPH

See Also

https://parsnip.tidymodels.org/reference/details_boost_tree_xgboost.html

Other Preprocessor: hai_c50_data_prepper(), hai_cubist_data_prepper(), hai_earth_data_prepper(), hai_glmnet_data_prepper(), hai_knn_data_prepper(), hai_ranger_data_prepper(), hai_svm_poly_data_prepper hai_svm_rbf_data_prepper()

Examples

```
library(ggplot2)
library(tibble)

# Regression
hai_xgboost_data_prepper(.data = diamonds, .recipe_formula = price ~ .)
reg_obj <- hai_xgboost_data_prepper(diamonds, price ~ .)
get_juiced_data(reg_obj)

# Classification
Titanic <- as_tibble(Titanic)

hai_xgboost_data_prepper(Titanic, Survived ~ .)
cla_obj <- hai_xgboost_data_prepper(Titanic, Survived ~ .)
get_juiced_data(cla_obj)
```

---

pca_your_recipe *Perform PCA*

Description

This is a simple function that will perform PCA analysis on a passed recipe.

Usage

```
pca_your_recipe(.recipe_object, .data, .threshold = 0.75, .top_n = 5)
```

Arguments

`.recipe_object`	The recipe object you want to pass.
`.data`	The full data set that is used in the original recipe object passed into `.recipe_object` in order to obtain the baked data of the transform.
`.threshold`	A number between 0 and 1. A fraction of the total variance that should be covered by the components.
`.top_n`	How many variables loadings should be returned per PC

Details

This is a simple wrapper around some recipes functions to perform a PCA on a given recipe. This function will output a list and return it invisible. All of the components of the analysis will be returned in a list as their own object that can be selected individually. A scree plot is also included. The items that get returned are:

1. pca_transform - This is the pca recipe.
2. variable_loadings
3. variable_variance
4. pca_estimates
5. pca_juiced_estimates
6. pca_baked_data
7. pca_variance_df
8. pca_rotattion_df
9. pca_variance_scree_plt
10. pca_loadings_plt
11. pca_loadings_plotly
12. pca_top_n_loadings_plt
13. pca_top_n_plotly

Value

A list object with several components.

Author(s)

Steven P. Sanderson II, MPH

See Also

https://recipes.tidymodels.org/reference/step_pca.html

Other Data Recipes: `hai_data_impute()`, `hai_data_poly()`, `hai_data_scale()`, `hai_data_transform()`, `hai_data_trig()`

Examples

```
suppressPackageStartupMessages(library(timetk))
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(purrr))
suppressPackageStartupMessages(library(healthyR.data))
suppressPackageStartupMessages(library(rsample))
suppressPackageStartupMessages(library(recipes))
suppressPackageStartupMessages(library(ggplot2))
suppressPackageStartupMessages(library(plotly))

data_tbl <- healthyR_data |>
  select(visit_end_date_time) |>
  summarise_by_time(
    .date_var = visit_end_date_time,
    .by       = "month",
    value     = n()
  ) |>
  set_names("date_col", "value") |>
  filter_by_time(
    .date_var = date_col,
    .start_date = "2013",
    .end_date = "2020"
  ) |>
  mutate(date_col = as.Date(date_col))

splits <- initial_split(data = data_tbl, prop = 0.8)

rec_obj <- recipe(value ~ ., training(splits)) |>
  step_timeseries_signature(date_col) |>
  step_rm(matches("(iso$)|(xts$)|(hour)|(min)|(sec)|(am.pm)"))

output_list <- pca_your_recipe(rec_obj, .data = data_tbl)
output_list$pca_variance_scree_plt
output_list$pca_loadings_plt
output_list$pca_top_n_loadings_plt
```

---

step_hai_fourier *Recipes Step Fourier Generator*

Description

step_hai_fourier creates a a *specification* of a recipe step that will convert numeric data into either a 'sin', 'cos', or 'sincos' feature that can aid in machine learning.

Usage

```
step_hai_fourier(
  recipe,
```

```
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  scale_type = c("sin", "cos", "sincos"),
  period = 1,
  order = 1,
  skip = FALSE,
  id = rand_id("hai_fourier")
)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose which variables that will be used to create the new variables. The selected variables should have class numeric
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new variable columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the quantities for preprocessing have been estimated.
columns	A character string of variables that will be used as inputs. This field is a placeholder and will be populated once recipes::prep() is used.
scale_type	A character string of a scaling type, one of "sin","cos", or "sincos"
period	The number of observations that complete a cycle
order	The fourier term order
skip	A logical. Should the step be skipped when the recipe is baked by bake.recipe()? While all operations are baked when prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.

Details

Numeric Variables Unlike other steps, step_hai_fourier does *not* remove the original numeric variables. recipes::step_rm() can be used for this purpose.

Value

For step_hai_fourier, an updated version of recipe with the new step added to the sequence of existing steps (if any).

Main Recipe Functions:

- recipes::recipe()
- recipes::prep()
- recipes::bake()

See Also

Other Recipes: step_hai_fourier_discrete(), step_hai_hyperbolic(), step_hai_scale_zero_one(), step_hai_scale_zscore(), step_hai_winsorized_move(), step_hai_winsorized_truncate()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

len_out <- 10
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

# Create a recipe object
rec_obj <- recipe(a ~ ., data = data_tbl) |>
  step_hai_fourier(b, scale_type = "sin") |>
  step_hai_fourier(b, scale_type = "cos") |>
  step_hai_fourier(b, scale_type = "sincos")

# View the recipe object
rec_obj

# Prepare the recipe object
prep(rec_obj)

# Bake the recipe object - Adds the Time Series Signature
bake(prep(rec_obj), data_tbl)

rec_obj |> get_juiced_data()
```

---

step_hai_fourier_discrete

Recipes Step Fourier Discrete Generator

Description

step_hai_fourier_discrete creates a a *specification* of a recipe step that will convert numeric data into either a 'sin', 'cos', or 'sincos' feature that can aid in machine learning.

Usage

```
step_hai_fourier_discrete(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  scale_type = c("sin", "cos", "sincos"),
  period = 1,
  order = 1,
  skip = FALSE,
  id = rand_id("hai_fourier_discrete")
)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose which variables that will be used to create the new variables. The selected variables should have class numeric or date,POSIXct
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new variable columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the quantities for preprocessing have been estimated.
columns	A character string of variables that will be used as inputs. This field is a placeholder and will be populated once recipes::prep() is used.
scale_type	A character string of a scaling type, one of "sin","cos", or "sincos"
period	The number of observations that complete a cycle
order	The fourier term order
skip	A logical. Should the step be skipped when the recipe is baked by bake.recipe()? While all operations are baked when prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.

Details

Numeric Variables Unlike other steps, step_hai_fourier_discrete does *not* remove the original numeric variables. recipes::step_rm() can be used for this purpose.

Value

For step_hai_fourier_discrete, an updated version of recipe with the new step added to the sequence of existing steps (if any).

Main Recipe Functions:

- recipes::recipe()
- recipes::prep()
- recipes::bake()

See Also

Other Recipes: step_hai_fourier(), step_hai_hyperbolic(), step_hai_scale_zero_one(), step_hai_scale_zscore(), step_hai_winsorized_move(), step_hai_winsorized_truncate()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

len_out <- 10
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

# Create a recipe object
rec_obj <- recipe(a ~ ., data = data_tbl) |>
  step_hai_fourier_discrete(b, scale_type = "sin") |>
  step_hai_fourier_discrete(b, scale_type = "cos") |>
  step_hai_fourier_discrete(b, scale_type = "sincos")

# View the recipe object
rec_obj

# Prepare the recipe object
prep(rec_obj)

# Bake the recipe object - Adds the Time Series Signature
bake(prep(rec_obj), data_tbl)

rec_obj |> get_juiced_data()
```

---

step_hai_hyperbolic *Recipes Step Hyperbolic Generator*

Description

step_hai_hyperbolic creates a a *specification* of a recipe step that will convert numeric data into either a 'sin', 'cos', or 'tan' feature that can aid in machine learning.

Usage

```
step_hai_hyperbolic(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  scale_type = c("sin", "cos", "tan", "sincos"),
  skip = FALSE,
  id = rand_id("hai_hyperbolic")
)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose which variables that will be used to create the new variables. The selected variables should have class numeric
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new variable columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the quantities for preprocessing have been estimated.
columns	A character string of variables that will be used as inputs. This field is a placeholder and will be populated once recipes::prep() is used.
scale_type	A character string of a scaling type, one of "sin","cos","tan" or "sincos"
skip	A logical. Should the step be skipped when the recipe is baked by bake.recipe()? While all operations are baked when prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.

Details

Numeric Variables Unlike other steps, step_hai_hyperbolic does *not* remove the original numeric variables. recipes::step_rm() can be used for this purpose.

Value

For step_hai_hyperbolic, an updated version of recipe with the new step added to the sequence of existing steps (if any).

Main Recipe Functions:

- recipes::recipe()
- recipes::prep()
- recipes::bake()

See Also

Other Recipes: step_hai_fourier(), step_hai_fourier_discrete(), step_hai_scale_zero_one(), step_hai_scale_zscore(), step_hai_winsorized_move(), step_hai_winsorized_truncate()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

len_out <- 10
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

# Create a recipe object
rec_obj <- recipe(a ~ ., data = data_tbl) |>
  step_hai_hyperbolic(b, scale_type = "sin") |>
  step_hai_hyperbolic(b, scale_type = "cos")

# View the recipe object
rec_obj

# Prepare the recipe object
prep(rec_obj)

# Bake the recipe object - Adds the Time Series Signature
bake(prep(rec_obj), data_tbl)

rec_obj |> get_juiced_data()
```

---

step_hai_scale_zero_one

Recipes Data Scale to Zero and One

Description

step_hai_scale_zero_one creates a a *specification* of a recipe step that will convert numeric data into from a time series into its velocity.

Usage

```
step_hai_scale_zero_one(
  recipe,
```

```
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  skip = FALSE,
  id = rand_id("hai_scale_zero_one")
)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.
...	One or more selector functions to choose which variables that will be used to create the new variables. The selected variables should have class numeric
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new variable columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the quantities for preprocessing have been estimated.
columns	A character string of variables that will be used as inputs. This field is a placeholder and will be populated once recipes::prep() is used.
skip	A logical. Should the step be skipped when the recipe is baked by bake.recipe()? While all operations are baked when prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.

Details

Numeric Variables Unlike other steps, step_hai_scale_zero_one does *not* remove the original numeric variables. recipes::step_rm() can be used for this purpose.

Value

For step_hai_scale_zero_one, an updated version of recipe with the new step added to the sequence of existing steps (if any).

Main Recipe Functions:

- recipes::recipe()
- recipes::prep()
- recipes::bake()

See Also

Other Recipes: step_hai_fourier(), step_hai_fourier_discrete(), step_hai_hyperbolic(), step_hai_scale_zscore(), step_hai_winsorized_move(), step_hai_winsorized_truncate()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

data_tbl <- data.frame(a = rnorm(200, 3, 1), b = rnorm(200, 2, 2))

# Create a recipe object
rec_obj <- recipe(a ~ ., data = data_tbl) |>
  step_hai_scale_zero_one(b)

# View the recipe object
rec_obj

# Prepare the recipe object
prep(rec_obj)

# Bake the recipe object - Adds the Time Series Signature
bake(prep(rec_obj), data_tbl)

rec_obj |>
  prep() |>
  juice()
```

---

step_hai_scale_zscore *Recipes Data Scale by Z-Score*

Description

step_hai_scale_zscore creates a a *specification* of a recipe step that will convert numeric data into from a time series into its velocity.

Usage

```
step_hai_scale_zscore(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  skip = FALSE,
  id = rand_id("hai_scale_zscore")
)
```

Arguments

recipe	A recipe object. The step will be added to the sequence of operations for this recipe.

...	One or more selector functions to choose which variables that will be used to create the new variables. The selected variables should have class numeric
role	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new variable columns created by the original variables will be used as predictors in a model.
trained	A logical to indicate if the quantities for preprocessing have been estimated.
columns	A character string of variables that will be used as inputs. This field is a placeholder and will be populated once recipes::prep() is used.
skip	A logical. Should the step be skipped when the recipe is baked by bake.recipe()? While all operations are baked when prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.

Details

Numeric Variables Unlike other steps, step_hai_scale_zscore does *not* remove the original numeric variables. recipes::step_rm() can be used for this purpose.

Value

For step_hai_scale_zscore, an updated version of recipe with the new step added to the sequence of existing steps (if any).

Main Recipe Functions:

- recipes::recipe()
- recipes::prep()
- recipes::bake()

See Also

Other Recipes: step_hai_fourier(), step_hai_fourier_discrete(), step_hai_hyperbolic(), step_hai_scale_zero_one(), step_hai_winsorized_move(), step_hai_winsorized_truncate()

Other Scale: hai_scale_zero_one_augment(), hai_scale_zero_one_vec(), hai_scale_zscore_augment(), hai_scale_zscore_vec()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

data_tbl <- data.frame(
  a = mtcars$mpg,
  b = AirPassengers |> as.vector() |> head(32)
)

# Create a recipe object
```

```
rec_obj <- recipe(a ~ ., data = data_tbl) |>
  step_hai_scale_zscore(b)

# View the recipe object
rec_obj

# Prepare the recipe object
prep(rec_obj)

# Bake the recipe object - Adds the Time Series Signature
bake(prep(rec_obj), data_tbl)

rec_obj |>
  prep() |>
  juice()
```

`step_hai_winsorized_move` *Recipes Step Winsorized Move Generator*

Description

`step_hai_winsorized_move` creates a a *specification* of a recipe step that will winsorize numeric data.

Usage

```
step_hai_winsorized_move(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  multiple = 3,
  skip = FALSE,
  id = rand_id("hai_winsorized_move")
)
```

Arguments

`recipe`	A recipe object. The step will be added to the sequence of operations for this recipe.
`...`	One or more selector functions to choose which variables that will be used to create the new variables. The selected variables should have class `numeric`
`role`	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new variable columns created by the original variables will be used as predictors in a model.

trained	A logical to indicate if the quantities for preprocessing have been estimated.
columns	A character string of variables that will be used as inputs. This field is a placeholder and will be populated once recipes::prep() is used.
multiple	A positive number indicating how many times the the zero center mean absolute deviation should be multiplied by for the scaling parameter.
skip	A logical. Should the step be skipped when the recipe is baked by bake.recipe()? While all operations are baked when prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.

Details

Numeric Variables Unlike other steps, step_hai_winsorize_move does *not* remove the original numeric variables. recipes::step_rm() can be used for this purpose.

Value

For step_hai_winsorize_move, an updated version of recipe with the new step added to the sequence of existing steps (if any).

Main Recipe Functions:

- recipes::recipe()
- recipes::prep()
- recipes::bake()

See Also

Other Recipes: step_hai_fourier(), step_hai_fourier_discrete(), step_hai_hyperbolic(), step_hai_scale_zero_one(), step_hai_scale_zscore(), step_hai_winsorized_truncate()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

len_out <- 10
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

# Create a recipe object
rec_obj <- recipe(b ~ ., data = data_tbl) |>
```

```
  step_hai_winsorized_move(a, multiple = 3)

# View the recipe object
rec_obj

# Prepare the recipe object
prep(rec_obj)

# Bake the recipe object - Adds the Time Series Signature
bake(prep(rec_obj), data_tbl)

rec_obj |> get_juiced_data()
```

`step_hai_winsorized_truncate`

Recipes Step Winsorized Truncate Generator

Description

`step_hai_winsorized_truncate` creates a a *specification* of a recipe step that will winsorize numeric data.

Usage

```
step_hai_winsorized_truncate(
  recipe,
  ...,
  role = "predictor",
  trained = FALSE,
  columns = NULL,
  fraction = 0.05,
  skip = FALSE,
  id = rand_id("hai_winsorized_truncate")
)
```

Arguments

`recipe`	A recipe object. The step will be added to the sequence of operations for this recipe.
`...`	One or more selector functions to choose which variables that will be used to create the new variables. The selected variables should have class `numeric`
`role`	For model terms created by this step, what analysis role should they be assigned?. By default, the function assumes that the new variable columns created by the original variables will be used as predictors in a model.
`trained`	A logical to indicate if the quantities for preprocessing have been estimated.

columns	A character string of variables that will be used as inputs. This field is a placeholder and will be populated once recipes::prep() is used.
fraction	A positive fractional between 0 and 0.5 that is passed to the stats::quantile paramater of probs.
skip	A logical. Should the step be skipped when the recipe is baked by bake.recipe()? While all operations are baked when prep.recipe() is run, some operations may not be able to be conducted on new data (e.g. processing the outcome variable(s)). Care should be taken when using skip = TRUE as it may affect the computations for subsequent operations.
id	A character string that is unique to this step to identify it.

Details

Numeric Variables Unlike other steps, step_hai_winsorize_truncate does *not* remove the original numeric variables. recipes::step_rm() can be used for this purpose.

Value

For step_hai_winsorize_truncate, an updated version of recipe with the new step added to the sequence of existing steps (if any).

Main Recipe Functions:

- recipes::recipe()
- recipes::prep()
- recipes::bake()

See Also

Other Recipes: step_hai_fourier(), step_hai_fourier_discrete(), step_hai_hyperbolic(), step_hai_scale_zero_one(), step_hai_scale_zscore(), step_hai_winsorized_move()

Examples

```
suppressPackageStartupMessages(library(dplyr))
suppressPackageStartupMessages(library(recipes))

len_out <- 10
by_unit <- "month"
start_date <- as.Date("2021-01-01")

data_tbl <- tibble(
  date_col = seq.Date(from = start_date, length.out = len_out, by = by_unit),
  a = rnorm(len_out),
  b = runif(len_out)
)

# Create a recipe object
rec_obj <- recipe(b ~ ., data = data_tbl) |>
  step_hai_winsorized_truncate(a, fraction = 0.05)
```

```
# View the recipe object
rec_obj

# Prepare the recipe object
prep(rec_obj)

# Bake the recipe object - Adds the Time Series Signature
bake(prep(rec_obj), data_tbl)

rec_obj |> get_juiced_data()
```

Index

∗ **Augment Function**
hai_fourier_augment, 46
hai_fourier_discrete_augment, 48
hai_hyperbolic_augment, 57
hai_polynomial_augment, 73
hai_scale_zero_one_augment, 78
hai_scale_zscore_augment, 80
hai_winsorized_move_augment, 89
hai_winsorized_truncate_augment, 92
∗ **Boiler_Plate**
hai_auto_c50, 7
hai_auto_cubist, 8
hai_auto_earth, 10
hai_auto_glmnet, 12
hai_auto_knn, 13
hai_auto_ranger, 15
hai_auto_svm_poly, 17
hai_auto_svm_rbf, 18
hai_auto_wflw_metrics, 20
hai_auto_xgboost, 21
∗ **C5.0**
hai_auto_c50, 7
hai_c50_data_prepper, 23
∗ **Color_Blind**
color_blind, 3
hai_scale_color_colorblind, 76
hai_scale_fill_colorblind, 77
∗ **Control Charts**
hai_control_chart, 24
∗ **Data Generation**
generate_mesh_data, 4
get_juiced_data, 5
∗ **Data Recipes**
hai_data_impute, 27
hai_data_poly, 29
hai_data_scale, 31
hai_data_transform, 33
hai_data_trig, 36
pca_your_recipe, 95
∗ **Data Wrangling**
pca_your_recipe, 95
∗ **Default Metric Sets**
hai_default_classification_metric_set, 37
hai_default_regression_metric_set, 38
∗ **Dimension Reduction**
pca_your_recipe, 95
∗ **Distribution Functions**
hai_distribution_comparison_tbl, 43
hai_get_density_data_tbl, 53
hai_get_dist_data_tbl, 54
∗ **Distribution Plots**
hai_density_hist_plot, 39
hai_density_plot, 40
hai_density_qq_plot, 41
∗ **Earth**
hai_auto_earth, 10
hai_earth_data_prepper, 45
∗ **Kmeans**
hai_kmeans_automl, 60
hai_kmeans_automl_predict, 62
hai_kmeans_mapped_tbl, 63
hai_kmeans_obj, 64
hai_kmeans_scree_data_tbl, 66
hai_kmeans_scree_plt, 67
hai_kmeans_tidy_tbl, 68
hai_kmeans_user_item_tbl, 70
∗ **Metric_Collection**
hai_auto_wflw_metrics, 20
∗ **Preprocessor**
hai_c50_data_prepper, 23
hai_cubist_data_prepper, 25
hai_earth_data_prepper, 45
hai_glmnet_data_prepper, 55
hai_knn_data_prepper, 71

hai_ranger_data_prepper, 74
hai_svm_poly_data_prepper, 84
hai_svm_rbf_data_prepper, 85
hai_xgboost_data_prepper, 94
* **Ranger**
hai_auto_ranger, 15
hai_ranger_data_prepper, 74
* **Recipes**
step_hai_fourier, 97
step_hai_fourier_discrete, 99
step_hai_hyperbolic, 101
step_hai_scale_zero_one, 103
step_hai_scale_zscore, 105
step_hai_winsorized_move, 107
step_hai_winsorized_truncate, 109
* **SVM_Poly**
hai_auto_svm_poly, 17
hai_svm_poly_data_prepper, 84
* **SVM_RBF**
hai_auto_svm_rbf, 18
hai_svm_rbf_data_prepper, 85
* **Scale**
hai_scale_zero_one_augment, 78
hai_scale_zero_one_vec, 79
hai_scale_zscore_augment, 80
hai_scale_zscore_vec, 81
step_hai_scale_zscore, 105
* **UMAP**
hai_umap_list, 86
hai_umap_plot, 88
* **Vector Function**
hai_fourier_discrete_vec, 49
hai_fourier_vec, 51
hai_hyperbolic_vec, 59
hai_kurtosis_vec, 72
hai_scale_zero_one_vec, 79
hai_scale_zscore_vec, 81
hai_skewness_vec, 83
hai_winsorized_move_vec, 90
hai_winsorized_truncate_vec, 93
* **XBGoost**
hai_xgboost_data_prepper, 94
* **XGBoost**
hai_auto_xgboost, 21
* **cubist**
hai_auto_cubist, 8
hai_cubist_data_prepper, 25
* **glmnet**
hai_auto_glmnet, 12
* **k-NN**
hai_auto_knn, 13
* **knn**
hai_glmnet_data_prepper, 55
hai_knn_data_prepper, 71

base::cbind(), *62*
broom::augment(), *68*
broom::glance(), *68*
broom::tidy(), *68*

color_blind, 3, *77, 78*

forcats::as_factor(), *62*

generate_mesh_data, 4, *6*
get_juiced_data, *5*, 5
ggrepel::geom_label_repel(), *88*

h2o::h2o.kmeans(), *60*
h2o::h2o.predict(), *62*
hai_auto_c50, 7, *9*, *11*, *13, 14*, *16*, *18–20*, *22*, *23*
hai_auto_cubist, *8*, 8, *11*, *13, 14*, *16*, *18–20*, *22*, *26*
hai_auto_earth, *8, 9*, 10, *13, 14*, *16*, *18–20*, *22*, *45*
hai_auto_glmnet, *8, 9*, *11*, 12, *14*, *16*, *18–20*, *22*
hai_auto_knn, *8, 9*, *11*, *13*, 13, *16*, *18–20*, *22*
hai_auto_ranger, *8, 9*, *11*, *13, 14*, 15, *18–20*, *22*, *75*
hai_auto_svm_poly, *8, 9*, *11*, *13, 14*, *16*, 17, *19, 20*, *22*, *85*
hai_auto_svm_rbf, *8, 9*, *11*, *13, 14*, *16*, *18*, 18, *20*, *22*, *86*
hai_auto_wflw_metrics, *8, 9*, *11*, *13, 14*, *16*, *18, 19*, 20, *22*
hai_auto_xgboost, *8, 9*, *11*, *13, 14*, *16*, *18–20*, 21
hai_c50_data_prepper, *8*, 23, *26*, *45*, *55*, *72*, *75*, *85, 86*, *95*
hai_control_chart, 24
hai_cubist_data_prepper, *9*, *23*, 25, *45*, *55*, *72*, *75*, *85, 86*, *95*
hai_data_impute, 27, *30*, *32*, *35*, *37*, *96*
hai_data_poly, *29*, 29, *32*, *35*, *37*, *96*
hai_data_scale, *29, 30*, 31, *35*, *37*, *96*

hai_data_transform, *29, 30*, *32*, 33, *37*, *96*
hai_data_trig, *29, 30*, *32*, *35*, 36, *96*
hai_default_classification_metric_set, *37*, *38*
hai_default_classification_metric_set(), *7*, *11, 12*, *14*, *16, 17*, *19*, *22*
hai_default_regression_metric_set, *38*, 38
hai_default_regression_metric_set(), *7*, *9*, *11, 12*, *14*, *16, 17*, *19*, *22*
hai_density_hist_plot, 39, *41, 42*
hai_density_plot, *39*, 40, *42*
hai_density_qq_plot, *39*, *41*, 41
hai_distribution_comparison_tbl, 43, *53, 54*
hai_earth_data_prepper, *11*, *23*, *26*, 45, *55*, *72*, *75*, *85, 86*, *95*
hai_fourier_augment, 46, *49*, *58*, *74*, *78*, *81*, *90*, *92*
hai_fourier_augment(), *52*
hai_fourier_discrete_augment, *47*, 48, *58*, *74*, *78*, *81*, *90*, *92*
hai_fourier_discrete_augment(), *50*
hai_fourier_discrete_vec, 49, *52*, *59*, *73*, *79*, *82*, *84*, *91*, *94*
hai_fourier_vec, *50*, 51, *59*, *73*, *79*, *82*, *84*, *91*, *94*
hai_get_density_data_tbl, *44*, 53, *54*
hai_get_dist_data_tbl, *44*, *53*, 54
hai_glmnet_data_prepper, *23*, *26*, *45*, 55, *72*, *75*, *85, 86*, *95*
hai_histogram_facet_plot, 56
hai_hyperbolic_augment, *47*, *49*, 57, *74*, *78*, *81*, *90*, *92*
hai_hyperbolic_augment(), *59*
hai_hyperbolic_vec, *50*, *52*, 59, *73*, *79*, *82*, *84*, *91*, *94*
hai_kmeans_automl, 60, *63–67*, *69, 70*
hai_kmeans_automl(), *62*
hai_kmeans_automl_predict, *61*, 62, *64–67*, *69, 70*
hai_kmeans_mapped_tbl, *61*, *63*, 63, *65–67*, *69, 70*
hai_kmeans_mapped_tbl(), *66, 67*, *87*
hai_kmeans_obj, *61*, *63, 64*, 64, *66, 67*, *69, 70*
hai_kmeans_obj(), *63*
hai_kmeans_scree_data_tbl, *61*, *63–65*, 66, *67*, *69, 70*
hai_kmeans_scree_plot (hai_kmeans_scree_plt), 67
hai_kmeans_scree_plt, *61*, *63–66*, 67, *69, 70*
hai_kmeans_scree_plt(), *66*
hai_kmeans_tidy_tbl, *61*, *63–67*, 68, *70*
hai_kmeans_user_item_tbl, *61*, *63–67*, *69*, 70
hai_kmeans_user_item_tbl(), *63–65*, *68*, *87*
hai_knn_data_prepper, *23*, *26*, *45*, *55*, 71, *75*, *85, 86*, *95*
hai_kurtosis_vec, *50*, *52*, *59*, 72, *79*, *82*, *84*, *91*, *94*
hai_kurtosis_vec(), *43*
hai_polynomial_augment, *47*, *49*, *58*, 73, *78*, *81*, *90*, *92*
hai_range_statistic, 76
hai_ranger_data_prepper, *16*, *23*, *26*, *45*, *55*, *72*, 74, *85, 86*, *95*
hai_scale_color_colorblind, *4*, 76, *78*
hai_scale_fill_colorblind, *4*, *77*, 77
hai_scale_zero_one_augment, *47*, *49*, *58*, *74*, 78, *79*, *81, 82*, *90*, *92*, *106*
hai_scale_zero_one_augment(), *79*
hai_scale_zero_one_vec, *50*, *52*, *59*, *73*, *78*, 79, *81, 82*, *84*, *91*, *94*, *106*
hai_scale_zscore_augment, *47*, *49*, *58*, *74*, *78, 79*, 80, *82*, *90*, *92*, *106*
hai_scale_zscore_augment(), *81*
hai_scale_zscore_vec, *50*, *52*, *59*, *73*, *78, 79*, *81*, 81, *84*, *91*, *94*, *106*
hai_skewed_features, 82
hai_skewness_vec, *50*, *52*, *59*, *73*, *79*, *82*, 83, *91*, *94*
hai_skewness_vec(), *43*
hai_svm_poly_data_prepper, *18*, *23*, *26*, *45*, *55*, *72*, *75*, 84, *86*, *95*
hai_svm_rbf_data_prepper, *19*, *23*, *26*, *45*, *55*, *72*, *75*, *85*, 85, *95*
hai_umap_list, 86, *88*
hai_umap_plot, *87*, 88
hai_winsorized_move_augment, *47*, *49*, *58*, *74*, *78*, *81*, 89, *92*
hai_winsorized_move_augment(), *91*
hai_winsorized_move_vec, *50*, *52*, *59*, *73*, *79*, *82*, *84*, 90, *94*
hai_winsorized_truncate_augment, *47*, *49*,

58, *74*, *78*, *81*, *90*, 92
hai_winsorized_truncate_augment(), *94*
hai_winsorized_truncate_vec, *50*, *52*, *59*, *73*, *79*, *82*, *84*, *91*, 93
hai_xgboost_data_prepper, *23*, *26*, *45*, *55*, *72*, *75*, *85*, *86*, 94

kmeans_mapped_tbl *(*hai_kmeans_mapped_tbl*)*, 63
kmeans_obj *(*hai_kmeans_obj*)*, 64
kmeans_scree_data_tbl *(*hai_kmeans_scree_data_tbl*)*, 66
kmeans_scree_plt *(*hai_kmeans_scree_plt*)*, 67
kmeans_tidy_tbl *(*hai_kmeans_tidy_tbl*)*, 68
kmeans_user_item_tbl *(*hai_kmeans_user_item_tbl*)*, 70

pca_your_recipe, *29*, *30*, *32*, *35*, *37*, 95
purrr::map(), *63*

recipes::step_BoxCox(), *34*
recipes::step_bs(), *35*
recipes::step_center(), *32*
recipes::step_hyperbolic(), *36*
recipes::step_impute_bag(), *27*, *28*
recipes::step_impute_knn(), *28*
recipes::step_impute_linear(), *28*
recipes::step_impute_lower(), *28*
recipes::step_impute_mean(), *28*
recipes::step_impute_median(), *29*
recipes::step_impute_mode(), *29*
recipes::step_impute_roll(), *29*
recipes::step_log(), *35*
recipes::step_logit(), *35*
recipes::step_normalize(), *32*
recipes::step_ns(), *35*
recipes::step_poly(), *30*
recipes::step_range(), *32*
recipes::step_relu(), *35*
recipes::step_rm(), *98*, *100*, *102*, *104*, *106*, *108*, *110*
recipes::step_scale(), *32*
recipes::step_sqrt(), *35*
recipes::step_YeoJohnson(), *35*
rlang::enquo(), *46*, *48*, *57*, *73*, *78*, *80*, *89*, *92*
rsample::mc_cv(), *7*, *9*, *11*, *12*, *14*, *16*, *17*, *19*, *22*

stats::kmeans(), *64*, *65*, *68*
stats::poly(), *74*
step_hai_fourier, 97, *101*, *103*, *104*, *106*, *108*, *110*
step_hai_fourier_discrete, *99*, 99, *103*, *104*, *106*, *108*, *110*
step_hai_hyperbolic, *99*, *101*, 101, *104*, *106*, *108*, *110*
step_hai_scale_zero_one, *99*, *101*, *103*, 103, *106*, *108*, *110*
step_hai_scale_zscore, *78*, *79*, *81*, *82*, *99*, *101*, *103*, *104*, 105, *108*, *110*
step_hai_winsorized_move, *99*, *101*, *103*, *104*, *106*, 107, *110*
step_hai_winsorized_truncate, *99*, *101*, *103*, *104*, *106*, *108*, 109

umap_list *(*hai_umap_list*)*, 86
umap_list(), *88*
umap_plt *(*hai_umap_plot*)*, 88
uwot::umap(), *86*, *87*