Package 'lfc'

September 28, 2026

Type Package

Title Log Fold Change Distribution Tools for Working with Ratios of Counts

Version 0.2.4

Description Ratios of count data such as obtained from RNA-seq are modelled using Bayesian statistics to derive posteriors for effects sizes. This approach is described in Erhard & Zimmer (2015) <doi:10.1093/nar/gkv696> and Erhard (2018) <doi:10.1093/bioinformatics/bty471>.

License Apache License (>= 2)

Encoding UTF-8

RoxygenNote 7.2.1

URL https://github.com/erhard-lab/lfc

BugReports https://github.com/erhard-lab/lfc/issues

Imports stats

Suggests knitr, rmarkdown, DESeq2, SummarizedExperiment

VignetteBuilder knitr

biocViews Bayesian, Transcriptomics, DifferentialExpression

NeedsCompilation no

Author Florian Erhard [aut, cre] (ORCID: <https://orcid.org/0000-0002-3574-6983>)

Maintainer Florian Erhard <Florian.Erhard@informatik.uni-regensburg.de>

Repository CRAN

Date/Publication 2026-09-27 23:00:02 UTC

Contents

CenterMedian 2
dlfc 3
EmpiricalBayesPrior 4

ltop 4
NormLFC 5
PsiLFC 6
PsiLFC.se 6
ptol 7
results 8

Index **9**

`CenterMedian` *Subtract the median of the given vector (for normalizing log2 fold changes).*

Description

Subtract the median of the given vector (for normalizing log2 fold changes).

Usage

```
CenterMedian(l)
```

Arguments

`l`	Vector of effect sizes

Value

A vector of length 2 containing the two parameters

See Also

PsiLFC

Examples

```
CenterMedian(rnorm(1000,200))
```

dlfc *The log2 fold change distribution*

Description

Density, distribution function, quantile function and random generation for the log2 fold change distribution with parameters 'a' and 'b' (corresponding to (pseudo-)counts incremented by 1).

Usage

```
dlfc(x, a, b, log = FALSE)

plfc(q, a, b, lower.tail = TRUE, log.p = FALSE)

qlfc(p, a, b, lower.tail = TRUE, log.p = FALSE)

rlfc(n, a, b)
```

Arguments

x, q	vector of quantiles
a	non-negative parameter
b	non-negative parameter
log, log.p	if TRUE, probabilities p are given as log(p)
lower.tail	if TRUE (default), probabilities are P[X <= x], otherwise, P[X > x].
p	vector of probabilities
n	number of observations

Value

The density

Functions

- dlfc(): Density function
- plfc(): Distribution function
- qlfc(): Quantile function
- rlfc(): random generation

Examples

```
x <- seq (-5,5,by=0.01)
plot(x,dlfc(x,1,1))
```

`EmpiricalBayesPrior` *Computes the prior parameters (i.e. pseudocounts incremented by 1) for the log2 fold change distribution*

Description

Computes the prior parameters (i.e. pseudocounts incremented by 1) for the log2 fold change distribution

Usage

```
EmpiricalBayesPrior(A, B, min.sd = 0)
```

Arguments

`A`	Vector of counts from condition A
`B`	Vector of counts from condition B
`min.sd`	minimal standard deviation of the prior

Value

A vector of length 2 containing the two parameters

See Also

PsiLFC

Examples

```
EmpiricalBayesPrior(rnorm(1000,200),rnorm(1000,100))
```

`ltop` *Inverse logit transformation to obtain proportion representation from the log fold change representation.*

Description

Inverse logit transformation to obtain proportion representation from the log fold change representation.

Usage

```
ltop(l)
```

Arguments

l	Effect size in log2 fold change representation

Value

The proportion representation of the effect size

See Also

ptol

Other Effect size representations: ptol()

Examples

```
ptol(0)
ptol(1)
```

NormLFC *Standard LFC effect size estimator*

Description

Computes the standard, normalized log2 fold change with given pseudocounts

Usage

```
NormLFC(A, B, pseudo = c(1, 1), normalizeFun = CenterMedian)
```

Arguments

A	Vector of counts from condition A
B	Vector of counts from condition B
pseudo	Vector of length 2 of the pseudo counts
normalizeFun	Function to normalize the obtained effect sizes

Value

The vector containing the estimates

Examples

```
NormLFC(rnorm(1000,200),rnorm(1000,100))
```

`PsiLFC` *Psi LFC effect size estimator*

Description

Computes the optimal effect size estimate and credible intervals if needed.

Usage

```
PsiLFC(
  A,
  B,
  prior = EmpiricalBayesPrior(A, B),
  normalizeFun = CenterMedian,
  cre = FALSE,
  verbose = FALSE
)
```

Arguments

`A`	Vector of counts from condition A
`B`	Vector of counts from condition B
`prior`	Vector of length 2 of the prior parameters
`normalizeFun`	Function to normalize the obtained effect sizes
`cre`	Compute credible intervals as well? (can also be a vector of quantiles)
`verbose`	verbose status updates?

Value

Either a vector containing the estimates, or a data frame containing the credible interval as well

Examples

```
PsiLFC(rnorm(1000,200),rnorm(1000,100))
```

`PsiLFC.se` *Psi LFC effect size estimator*

Description

Computes the optimal effect size estimate and credible intervals if needed for a Bioconductor SummarizedExperiment object

Usage

```
PsiLFC.se(se, contrast, cre = FALSE)
```

Arguments

se	SummarizedExperiment object
contrast	Vector of length 3 (<name>,<A>,<B>)
cre	Compute credible intervals as well? (can also be a vector of quantiles)

Value

Either a vector containing the estimates, or a data frame containing the credible interval as well

Examples

```
## Not run:
   data(airway, package="airway")
   head(PsiLFC.se(airway,contrast=c("dex","untrt","trt")))

## End(Not run)
```

---

ptol *Logit transformation to obtain the log fold change representation from the proportion representation.*

Description

Logit transformation to obtain the log fold change representation from the proportion representation.

Usage

```
ptol(p)
```

Arguments

p	Effect size in proportion representation

Value

The log2 fold change representation of the effect size

See Also

ltop

Other Effect size representations: `ltop()`

Examples

```
ptol(0.5)
ptol(2/3)
```

`results` *Psi LFC effect size estimator for DESeq2*

Description

Drop-in replacement for DESeq2's results function for simple settings involving a single variable. Appends the PsiLFC estimate.

Usage

```
results(object, contrast, cre = FALSE, ...)
```

Arguments

`object`	the DESeq2DataSet object
`contrast`	Vector of length 3, specifying the variable and the two levels to compute effect sizes for (<name>,<A>,<B>)
`cre`	Compute credible intervals as well? (can also be a vector of quantiles)
`...`	Handed over to DESeq2's results function

Value

Either a vector containing the estimates, or a data frame containing the credible interval as well

Index

∗ **Effect size representations**
ltop, 4
ptol, 7
∗ **Log2 fold change distribution**
dlfc, 3

CenterMedian, 2

dlfc, 3

EmpiricalBayesPrior, 4

ltop, 4, *7*

NormLFC, 5

plfc *(*dlfc*)*, 3
PsiLFC, 6
PsiLFC.se, 6
ptol, *5*, 7

qlfc *(*dlfc*)*, 3

results, 8
rlfc *(*dlfc*)*, 3